

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
 NEW MEXICO OIL CONSERVATION COMMISSION
AUG 31 1979
O. C. C.
ARTESIA, OFFICE

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-3529
7. Unit Agreement Name
8. Farm or Lease Name State "25" Com.
9. Well No. 1
10. Field and Pool, or Wildcat Turkey Track (Morrow)
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Southland Royalty Company ✓ 3. Address of Operator 1100 Wall Towers West, Midland, Texas 79701 4. Location of Well UNIT LETTER <u>L</u> 1980 FEET FROM THE <u>south</u> LINE AND <u>2130</u> FEET FROM THE <u>west</u> LINE, SECTION <u>25</u> TOWNSHIP <u>19-S</u> RANGE <u>29-E</u> NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3339.0' GR	RECEIVED SEP 7 1979 O. C. C. ARTESIA, OFFICE
---	---

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud by Hondo Drilg. Co. Rig #5 @ 9:00 PM 8-21-79. Drill 15" hole to 413'. Ran 11 3/4" 42# H-40 ST&C. Csg. set to 412'. Cement w/400 sx Class "C" cement w/2% c.c. Plug down @ 12:15 PM 8-22-79. Cement circulated. Install double 10" ser 900 BOP. Test casing and BOP to 1000 psi for 30 min, hold O.K. Drill ahead 11" hole.

Note: W.O.C. 18 hrs prior to testing BOP and csg.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. Harney Can TITLE District Engineer DATE 8-28-79
 APPROVED BY W. A. Gussitt TITLE SUPERVISOR, DISTRICT #1 DATE SEP 7 1979
 CONDITIONS OF APPROVAL, IF ANY: