

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED

SEP 2 1980

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
OG-783

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER- _____

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
207 So. 4th St., Artesia, NM 88210

4. Location of Well
UNIT LETTER C 990 FEET FROM THE North LINE AND 2310 FEET FROM
THE West LINE, SECTION 5 TOWNSHIP 19S RANGE 25E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name
Greewood BD State

9. Well No.
10

10. Field and Pool, or Wildcat Assoc
Penasco Draw SA Yeso

15. Elevation (Show whether DF, RT, GR, etc.)
3583' GR

12. County
Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS OTHER

TEMPORARILY ABANDON

PULL OR ALTER CASING

SUBSEQUENT REPORT OF:

REMEDIAL WORK ALTERING CASING

COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT

CASING TEST AND CEMENT JOBS

OTHER

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 15" hole at 5:30 p.m. 8-28-80.
TD 410'- Ran 9 jts 10-3/4" - 40.5# J-55 casing (413') set at 410'. 1 cut off shoe at 410' and flapper float at 361'. Cemented with 300 sx Class C 4% CaCl. PD 2:30 a.m. 8-29-80. Cement did not circulate. Filled hole w/8 yards Ready Mix. WOC 12 hours, reduced hole to 9-1/2". Drilled plug and tested to 600#. Ok. Resumed drilling.
TD 992' - Ran 23 jts 7" - 20# K-55 casing (994'). Set at 992'. 1 Texas pattern guide shoe at 992' and flapper float at 948'. Cemented with 200 sx Class C Neat, 800 sx 65-35 Poz 4% gel 3% CaCl, 8# keolite, 1/4# celloflake. Tailed in with 150 sx Class C 2% CaCl. PD 2:00 p.m. 8-30-80. Cement did not circulate. WOC 6 hrs and ran temperature survey. Top cement at 400'. Ran 1" tagged cement at 400', spt'd 25 sx Class C 4% CaCl. PD 9:30 a.m. 8-30-80. WOC 2 hrs, ran 1", tagged cement at 357', spt'd 25 sx Class C 4% CaCl PD 11:30 p.m. 8-30-80. WOC 2 hrs, ran 1", tagged cement at 357', spt'd 100 sx Class C 4% CaCl. PD 2:15 a.m. 8-31-80. Circulated 2 sx to pit. WOC 18 hrs. NU, tested to 1500# - OK, reduced hole to 6-1/4", drilled plug, tested to 600# - OK. Resumed drilling

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Albert R. Hall TITLE Engineer DATE 9/2/80

APPROVED BY W.A. Gussert TITLE SUPERVISOR, DISTRICT 11 DATE SEP 5 - 1980

CONDITIONS OF APPROVAL, IF ANY: