

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

CANTRO EXPLORATION, INC.

3. ADDRESS OF OPERATOR

PO BOX 700150, SAN ANTONIO, TX 78270

AGENT: PO BOX 196 ARTESIA, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

330' FNL AND 1650' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3511' GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

PUMPED THE FOLLOWING PLUGS TO ABANDON THE ABOVE CAPTIONED WELL. ALL PLUGS INSIDE 5½" CASING. THE CEMENT ON THE 5½" CASING WAS CIRCULATED TO SURFACE WHEN RUN.

- PRODEDURE #1 PUMPED 25 SX CLASS C CEMENT FROM 2380' TO 2148'. ALLOW TO SET 2 HRS. AND TAG.
- #2 PUMPED 5 SX CLASS C CEMENT FROM 2038' TO 1988'. BASE SALT.
- #3 PUMPED 5 SX CLASS C CEMENT FROM 758' TO 708'. TOP SALT.
- #4 PUMPED 10 SX CLASS C CEMENT FROM 350' TO 250'. 50' BELOW AND ABOVE SURFACE CASING SHOE.
- #5 PUMPED 5 SX CLASS C CEMENT TO SURFACE.

DRY HOLE MARKER HAS BEEN INSTALLED AND SURFACE LOCATION WAS RESTORED AND SEEDED.

\*THIS WELL WAS P & A 10-4-88 AND APPROPRIATE PAPERWORK WAS FILED. THIS FILING IS TO NOTIFY YOU THAT THE LEASE NUMBER HAS BEEN INSTALLED ON THE DRY HOLE MARKER AS OF 11-10-93.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE C.E. LARUE - AGENT

DATE 11-11-93

(This space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS

TITLE

Petroleum Engineer

DATE 11-11-93

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.