

215F

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

5. LEASE	NM-45227
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME	Chevron Federal Comm.
9. WELL NO.	1
10. FIELD OR WILDCAT NAME	Undesignated Penn
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	Sec. 5, T19S, R27E
12. COUNTY OR PARISH	Eddy
13. STATE	NM
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD)	3280 GL

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to d... or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Robert N. Enfield

3. ADDRESS OF OPERATOR
P.O. Box 2431, Santa Fe, NM 87504-2431

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1835' FNL & 2310' FWL of Sec. 5

AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

RECEIVED BY
MAY 22 1986
O. C. D.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <u>SPUD * SURFACE CASING X</u>	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well was spudded 7:00 AM March 25, 1986.
Reached TD of 305' at 3:45 PM March 25, 1986.
Ran 13-3/8", 54.50#/ft., J-55 ST&C casing, set at 305', cemented w/300 sacks Class "C" with 2% CACL2. Plug down at 8:00 PM March 25, 1986 with full circulation. Circulated 20 sacks to surface.
Tested blind rams with 600 PSIG for 1/2 hr., tested OK.
Tested pipe rams with 600 PSIG for 1/2 hr., tested OK.

ACCEPTED FOR RECORD
MAY 21 1986

Subsurface Safety Valve: Manu. and Type CARLSBAD, NEW MEXICO Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct
SIGNED Robert N. Enfield TITLE Operator DATE 5/19/86
Robert N. Enfield

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: