

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Robert N. Enfield

3. ADDRESS OF OPERATOR

P.O. Box 2431, Santa Fe, NM 87501

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980' FNL & 990' FEL of Sec. 7  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Daily Drilling

SUBSEQUENT REPORT OF:

5. LEASE

NM-29826

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Walters Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Undes McMillan U.Penn(Gas)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 7, T19S, R27E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

14. API NO.

15. ELEVATIONS (SHOW CF, KDB, AND WD)  
3271' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10/24/87 Drilled from 2195' - 2420' Deviation 1° 2230', 1/2° 2382'. Ran 2421.30' KB 8-5/8" 24# J-55 ST&C casing. Cemented w/900 sx Howco Lite w/5# gilsonite/sx & 1/4# flocele/sx plus 300 sx Class H w/2% CACL2 & 1/4# flocele/sx. Plug down 2:15 AM 10/24/87. Circulated 140 sx to pit. Witnessed by Danny Cortez, BLM, Carlsbad.

10/25/87 Drilling at 2580', tested casing to 1000#, held OK

10/26/87 Drilling at 3190'. Deviation 2654' 1/2°, 2996' 1/2°

10/27/87 Drilling at 3730'. Deviation 3370' 1-1/4°, 3588' 1°

10/28/87 Drilling at 4110'. Deviation 3712' 3/4°, 3904' 3/4°

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert N. Enfield

Operator

DATE 11/11/87

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

RECORDED

NOV 17 1987