

SUNDRY NOTICES AND REPORTS ON WELLS

See back for instructions on how to fill out this form for reports on wells or for applications for permits to drill or to operate or plug wells in the State of New Mexico.

Oil ☒ Gas ☐ Other ☐

Name of Operator

Siete Oil & Gas Corporation

Address of Operator

P.O. Box 2523

Roswell, NM 88202-2523

Location of Well (Report location clearly and in accordance with any State regulations. See also space 37 below.)

At Surface

2230' FNL & 760' FWL, SW $\frac{1}{4}$ NW $\frac{1}{4}$, Unit Letter E

DEC 6 11 11 AM '88

CARLSBAD OFFICE

RECEIVED

FEB 16 '90

Phone No

30-015-26006

Well Elevations (Show whether on, off, or in.)

3312' GR

ARTESIAN OFFICE

1. Well Completion Date

2. Name of Lease Owner

Renegade Federal

3. Well No.

3

4. Name and Address of Well Owner

Parkway Delaware

5. Sec. 35: T19S, R29E

6. County or Parish

Eddy

7. State

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

FRACTURE TEST

SHUT-IN ACIDIZING

REPAIR WELL

(Other)

WELL OR ALTER CASING

MULTIPLE COMPLETIONS

ABANDON

CHANGE PLANE

☐
☐
☐
☐

COMPLETION REPORT ON:

WATER SHUT-OFF

☐
☒
☒

FRACTURE TREATMENT

SHUT-IN ACIDIZING

(Other) TD, Prod Csg, Logging

REPAIRING WELL

ALTERING CASING

ABANDONMENT

☐
☐
☒

(Note: Report results of multiple completions on Well Completion or Recombination Report and Log form.)

37. Describe proposed or completed operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give substantial headings and measured and true vertical depths for all markers and open ports (omit in this work).)

- 11/29/88 TD 7 7/8" hole to 5000' @ 10:00 AM, TOH w/bit #6 @ 5000', RU Schlumberger & ran DLL/MSFL, LDT/CNL & Cyberlook logs on interval 50'-4997', logger's TD @ 5000'.
- 11/30/88 RU & ran 120 jts (5017') 5 1/2" 15.5# J-55 csg, set @ 5000', cemented w/450 sks tail-in Std w/.7% D-127 Fla, 5# D-44, PD @ 9:15 PM, released rig @ 11:00 PM.
- 12/02/88 RU Schlumberger & ran CBL, perfed Delaware interval 4557'-4578' w/15 perfs, TIH w/SN & 2 3/8" tbg.
- 12/03/88 Spot 2 bbls acid over perfs, set SN @ 4491', formation broke @ 2100, acidized w/1000 gal 15% KCl, divert w/30 ballsealers, AIR-3 BPM, AIP-1650, max-3470 (balled out), FPIP-1415, ISIP-1030, fraced w/18,000 gal 30# XL, 2000# 100 mesh, 27,000# 20/40, 12,000# 12/20, AIR-7.1 BPM, AIP-2400, FPIP-1524, ISIP-1085, max-2714, @ 5 min-1034, @ 10 min-1012, @ 15 min-998, TIH w/tbg to 4524' reset SN @ 4524', began swabbing.

ACCEPTED FOR RECORD

DEC 15 1988

CONFIDENTIAL

CARLSBAD, NEW MEXICO

38. I hereby certify that the foregoing is true and correct

SIGNED Cathy Batley

TITLE Drilling/Production Secretary

DATE 12/5/88

(This space for Federal or State other use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side