

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ARTESIA, NM 88210

SUBMIT IN TRI
(Other Instructions
verse side)

DATE
on re

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

clsf

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

5. LEASE DESIGNATION AND SERIAL NO.

NM 58143

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Cholla AGE Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat (MORROW)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit I, Sec. 3-T20S-R24E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

MAY 30 '89

3. ADDRESS OF OPERATOR

105 South 4th St., Artesia, NM 88210

O. C. D.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

2080' FSL & 660' FEL, NE/SE, Sec. 3-20S-24E

14. PERMIT NO.

API #30-015-26071

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3692.7' GR

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING ☒

ABANDONMENT*

(Other) Perforate, Treat

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 9440'

5-4-89. RUPU. Tagged cement to 5737' and DV tool at 5750'. Drilled retainer and continue in hole to 9380'.

5-5-89. WIH and perforated 9274-9290' w/10 - .42" holes as follows: 9274, 78, 79, 84, 85, 86, 87, 88, 89 and 9290'.

5-8-89. Acidized perforations 9274-90' w/2500* gals 15% NEFE acid and 15 ball sealers

*AMENDED REPORT TO CORRECT VOLUME OF ACID USED TO TREAT WELL.

RECEIVED
MAY 12 11 07 AM '89

18. I hereby certify that the foregoing is true and correct

SIGNED

John A. Souders

TITLE Production Supervisor

DATE 5-11-89

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

SJS