

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT, COMMISSION

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

dsf

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
Yates Petroleum Corporation

3. ADDRESS OF OPERATOR
105 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
2080' FSL & 660' FEL, NE/SE, sec. 3-20S-24E

14. PERMIT NO.
API 30-015-26071

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3692.7' GR

JUN 08 '89

O. C. M.

ARTESIA OFFICE

5. LEASE DESIGNATION AND SERIAL NO
NM 58143

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Cholla AGE Federal

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Wildcat Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit I, Sec. 3-T20S-R24E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

5-5-89. WIH and perforated 9274-9290' w/10 - .42" holes as follows: 9274, 78, 79, 84, 85, 86, 87, 88, 89 and 9290'. Perforated Morrow sand 9093-98' w/10 - .42" holes (2 SPF).

5-8-89. Acidized perforations 9274-90' w/2500 gals 15% NEFE acid and 15 ball sealers.

5-11-89. Acidized Morrow perforations 9093-98' w/2000 gals 7½% acid and 10 ball sealers.

5-12-89. Swabbed well.

5-19-89. Sand frac'd Morrow perforations 9093-98' w/29000 gals X-link gel, 10000 gals CO2 and 27500# 20/40 sand.

5-26-89. Set RBP 8211' and test to 4000#, OK. Perforated Canyon w/16 - .42" holes as follows: 7743, 46, 52, 53, 55, 57, 58, 61, 62, 64, 65, 71, 72, 73, 75 and 7776'.

5-30-89. Acidized perforations 7743-76' w/4000 gals 20% NEFE acid.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Supervisor

DATE 5-31-89

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

536