

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

5. Lease Designation and Serial No.

44-00559175

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

SUBMIT IN TRIPLICATE

DEC 7 '90

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Conoco Inc.

O. C. D.
ARTESIA, OFFICE

3. Address and Telephone No.

10 Desta Drive W. Midland, TX 79705 (915)686-6553

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FWL UNIT LTR E SECT. 30. T-19S R-25E

8. Well Name and No.

DAGGER DRAW COM NO 9

9. API Well No.

30-015-26489

10. Field and Pool, or Exploratory Area

NO DAGGER DRAW-UP FN

11. County or Parish, State

EDDY, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☒ Altering Casing
☐ Other PRODUCTION CASING
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

DRILLED 8 3/4" HOLE TO 8110' (TD). LOGGED WELL.
RAN IN HOLE WITH 189 JTS OF 2" 26 # X-55 CASING TO 8108'.
FIRST STAGE OF CEMENTING UTILIZED 620 SXS OF CLASS H (35:65:6) 1% FL20 + 2% A-7. TRAILLED BY 330 SXS OF CLASS H 3% A-7 + 1% FL20 + 1% A-7.
SECOND STAGE OF CEMENTING UTILIZED 380 SXS OF CLASS H (35:65:6) 1% FL20 + 2% A-7. TRAILLED BY 250 SXS OF CLASS H 3% A-7 + 1% FL20 + 1% A-7.
TRAILLED 133 SXS OF CEMENT TO SURFACE ON SECOND STAGE OF CEMENTING.
OUT OFF 2" CASING. RELEASED RIG.

14. I hereby certify that the foregoing is true and correct

Signed

Nannette Nelson

Title

Analyst - Oil Production

Date

11-29-1990

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

RECEIVED
DEC 3 10 45 AM '90
CARTER
AREA