Form C-103 State of New Mexico Revised 1-1-89 Submit 3 Copies L gy, Minerals and Natural Resources Departme. to Appropriate District Office OIL CONSERVATION DIVISION WELL API NO. DISTRICT P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-015-27633 Santa Fe, New Mexico 87504-2088 5. Indicate Type of Lease DISTRICTI FEE X P.O. Drawer DD, Artesia, NM 88210 STATE OCT 2.2 1993 6. State Oil & Gas Lease No. DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 À 6 D. SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Patriot AIZ Com WELL X OTHER WELL 8. Well No. 2. Name of Operator YATES PETROLEUM CORPORATION 3 9. Pool name or Wildcat Address of Operator North Dagger Draw Upper Penn 105 South 4th St., Artesia, NM 88210 (505) 748-1471Well Location Feet From The __East Line and 660 Line South 760 Feet From The Unit Letter __ County 25E Eddy **NMPM** 19S Range 20 Township Section 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3513' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: ALTERING CASING REMEDIAL WORK PLUG AND ABANDON PERFORM REMEDIAL WORK PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. CHANGE PLANS TEMPORARILY ABANDON CASING TEST AND CEMENT JOB PULL OR ALTER CASING OTHER: Production Casing OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. TD 8330'. Reached TD 10-15-93. Ran 204 joints 7" 23# and 26# J-55 and N-80 casing set 8330'. Float shoe set 8330', float collar set 8288'. DV tool set 5611'. Cemented in two stages: Stage I - 625 sx Class "H" w/5#/sx Gilsonite, 5#/sx CSE, 1/4#/sx Celloseal, .65% CF-14 (yield 1.31, wt 15.1). PD 5:35 PM 10-16-93. Bumped plug to 1250 psi for 1 minute. Circulated 130 sacks. Stage II - 800 sx PSL "C" (65/35/6) with 5#/sx Gilsonite, 1/4#/sx Celloseal, .4% CF-14 (yield 1.98, wt 12.9). Tailed in w100 sx Class "H" Neat (yield 1.17, wt 15.6). PD 10:18 PM 10-16-93. Bumped plug to 2000 psi for 3 minutes, OK. Circulated 113 sacks. WOC 18 hours.

TIME Production Supervisor

DATE __10-20-93

TELEPHONE NO.505/748-1471

NOV 1 8 1993

TYPE OR PRINT NAME

APPROVED BY-

(This space for State Use)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY

SUPERVISOR DISTRICT IT

MIKE WILLIAMS

Juanita Goodlett