



NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

William Dooley and Ira Dixon
Company or Operator
Commerce
Address
Commerce
Well No. 1 in NW of Sec. 18, T. 20
R. 26 N. M. P. M., Globe Field, Eddy County.
Well is 600 feet south of the North line and 330 feet east of the East line of section 18
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Commerce Trust Company Address Kansas City, Mo.
If Government land the permittee is Address
The Lessee is Address
Drilling commenced January 2 19 36 Drilling was completed June 11 19 36
Name of drilling contractor Ira Dixon Address Artesia, New Mexico
Elevation above sea level at top of casing 3347 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES
No. 1, from Light gas 888 to 407
No. 2, from 827 to 958
No. 3, from Rainbow showings to
No. 4, from to
No. 5, from to
No. 6, from to

IMPORTANT WATER SANDS (or line)
Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from 100 to 370 feet. Did not rise in casing
No. 2, from 827 to 948 feet. Seeps and light water
No. 3, from 948 to 958 feet. Rose about 900'
No. 4, from to feet.

CASING RECORD									
SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
No casing left in hole. All casing was pulled before plugging well.									

MUDDING AND CEMENTING RECORD in plugging well
SIZE OF HOLE SIZE OF CASING WHERE SET NO. SACKS OF CEMENT METHOD USED MUD GRAVITY AMOUNT OF MUD USED
6 5/8 bottom of hole 3 dumped cem. with bailer Heavy mud from top of cem. (Second cement plug set at 390') plug to 390'.
8 1/4 390 3 dumped with bailer
(Heavy mud from top of second cement plug to top of hole)

PLUGS AND ADAPTERS
Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT						
SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Did not shoot or treat chemically.				

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS
If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED
Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from 0 feet to 958 feet, and from feet to feet

PRODUCTION (No production)
Put to producing 19
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES
Ira Dixon Driller
Red Wedges Driller

FORMATION RECORD ON OTHER SIDE
I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.
Subscribed and sworn to before me this 12 Artesia, New Mexico June 12, 1936
day of June 19 36 Name William Dooley

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	75		Gyp
75	110		lime
110	125		Gyp
125	140		lime and shale
140	160		Gumbo
160	165		Sandy lime
165	180		Gumbo
180	225		lime
225	529		Dolomite
529	539		Sandy shale
539	649		Dolomite
649	665		Sand and shale
665	777		Dolomite
777	788		Brown lime with little blue shale
788	856		Dolomite
856			Total depth