

Form 3160-5  
(June 1990)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ARTESIA, NEW MEXICO

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM01119

6. If Indian, Allottee or Tribe Name

7. If Unit of Agreement Designation

Welch Federal

8. Well Name and No.

Riggs 3 #3

9. API Well No.

3001501069

10. Field and Pool, or Exploratory Area

Cedar Hills

11. County or Parish, State

Eddy, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil ☐ Gas ☐ Other

2. Name of Operator

Bill Taylor

3. Address and Telephone No.

1106 N. Country Club, Carlsbad, NM 88220

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2970' FSL & 990' FEL Sec. 5, T21S, R27E, NMPM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other **Plugged Well**

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7/12/99: Placed 25 sks. cement through 1" tubing at 509'. Tagged top of cement at 391'. Plug is a solid, good barrier seal between the lower level oil and upper level water! Cement is in open hole, 406' to bottom.

7/23/99: Placed 25 sks. cement through 1" tubing at 391'.

7/24/99: Top of cement tagged at 301'. Placed 25 sks. cement through 1" at 301'.

7/26/99: 1" tubing bottomed at 268'. Placed bentonite and loss circulation material in hole, followed by cement.

7/29/99: 1" tubing bottomed at 218'. Pumped fresh water into hole, followed by 25 sks. cement.

7/30/99: Tagged top of cement at 38'. Placed 7 sks. cement through 1" tubing; placed 4" pipe into cement to weld dry hole marker on. Cement down 3' from ground level.

8/06/99: Welded dry hole marker to 4" pipe in plugged well. Placed 5 sks. cement to bring cement to surface.

Carlsbad BLM was given advance notices of cementing.

14. I hereby certify that the foregoing is true and correct

Signed

Bill Taylor

Title

Operator

Date

8/13/99

(This space for Federal or State office use)

ORIG. SGD. GARY GOURLEY

Title

PETROLEUM ENGINEER

Date

Approved by  
Conditions of approval, if any: