NEW _XICO OIL CONSERVATION COMM ION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

indicate nature of	notice by checking below:		
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO S CHEMICALLY TREAT WE		
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO OTHERWISE ALTER CAS		
OTICE OF INTENTION TO REPAIR WELL			
OTICE OF INTENTION TO DEEPEN WELL	NOTICE OF INTENTION TO	PLUG WELL	X
	Place	Date	
IL CONSERVATION COMMISSION, anta Fe, New Mexico			
entlemen: following is a notice of intention to do certain work as			
Company or Operator Lea	Well No.	in N	Sec
Company of operator			Field,
f Sec. 15 , T. 218 , R. 27E	, IV. IVI. F. IVI.,		rieiu,
Eddy County.			
FULL DETAILS OF P	ROPOSED PLAN OF WORK		
FOLLOW INSTRUCTIONS IN THE RUL		MMISSION	
FOLLOW INSTRUCTIONS IN THE NOT			
ug well with cement, 20 sacks, f id, saturated lime encountered 57 accountered sulphur water	rom TD 583' back up to 6' to 580', but upon do	rilling t	o 583
id, saturated lime encountered 57	rom TD 583' back up to 6' to 580', but up n d	rilling t	o 583 '
d, saturated lime encountered 57	rom TD 583' back up to 6' to 580', but up n d	rilling t	o 583
d, saturated lime encountered 57	rom TD 583' back up to 6' to 580', but up n d	rilling t	o 583 °
d, saturated lime encountered 57	rom TD 583' back up to 6' to 580', but up n d	rilling t	o 583 °
d, saturated lime encountered 57	rom TD 583' back up to 6' to 580', but up n d	rilling t	o 583 •
d, saturated lime encountered 57 countered sulphur water	R S Wagruder	rilling t	o 583 '
d, saturated lime encountered 57 countered sulphur water	R S Wagruder	rilling t	o 583 °
d, saturated lime encountered 57 countered sulphur water	R S Magruder	rilling t	o 583 °
d, saturated lime encountered 57 countered sulphur water	R S Magruder	rilling t	o 583 °
d, saturated lime encountered 57 countered sulphur water	R 8 Magrader Company or poerat By	rilling t	o 583 '
d, saturated lime encountered 57 countered sulphur water	R S Wattuder Company or poerat	rilling t	o 5 83
d, saturated lime encountered 57 scountered sulphur water	R 8 Magrader Company or operat By Position	rilling t	o 5 83
Approved	R S Magruder Company or operat By Position Send communications re	rilling t	o 5 83 '