Form 3160-5 (November 1983) (Formerly 9-331)	DEPARTMEN	D STATES OF THE INTERIOR AND MANAGEMENT	SUBMIT IN TRIPI (E- (Other instructions re verse side)	5. LEASE DESIGNATION	eu No. 1004–0135 () ist 31, 1985	
(Do not use th		ND REPORTS ON		6. IF INDIAN, ALLOT		
OIL GAS WELL WELL NAME OF OPERATOR				7. UNIT AGREEMENT NAME Saladar Unit 8. FARM OR LEASE NAME		
Barber 8. ADDRESS OF OPERAT	O11, Inc ox 1658 Carlsbac (Report location clearly and selow.)	9. WBLL NO. 9 10. FIRLD AND POOL, OR WILDCAT				
Unit Letter (0) 660' FSL and 2310' FEL				11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 33, T20S, R28E		
14. PERMIT NO.	15. BLEVATIONS (Show whether DF, RT, GR, etc.) 3205 GR			12. COUNTY OR PART Eddy	-	
16.	Check Appropriate Box To Indicate Nature of Notice, Report, or NOTICE OF INTENTION TO:				Other Data	
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other) 17. DESCRIBE PROPOSED proposed work, nent to this work	OR COMPLETED OPERATIONS (If well is directionally drill	ANS Clearly state all particult de	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (NOTE: Report result Completion or Recomp tails, and give pertinent dates and measured and true vertice	REPAIRIN ALTERING ARANDON: s of multiple completic pletion Report and Log , including estimated cal depths for all mari	CASING X	
4/17/90- 4/18/90-	casing and casing 50 sax cement. Ran tubing and t	ng borke at 4'. R Shut down. agged cement at 3 de and inside of c	ion. Pulled tubing an tubing to botton to the second to the second to the second tensor tenso	om of hole and casing at 50'	circulated	
	Company Witness: David Walker BLM Witness: Cathey Queen		RECEV	SD AREA	7.1 Jul 20	
			JUL 27	7 '90 E	ECEIVED	
			O. C ABTUSIA 31	OFFICE PRODUCT	90	
18. I hereby certify th	$2 \Omega \Omega$	correct		·	Pat ID-2 7-27-90 P+A	
SIGNED SIGNED	dalle		esident	DATE	19/90	
(This space for Fe	deral or State onde use) Signed Ly Aliam Salameh APPROVAL, IF ANY:	TITLE	region Element	DATE	25 90	
	d Pare and the	ore.		,		

Approved as to publing of the well to Liability under bond is retained until surface restoration is completed.

*See Instructions on Reverse Side