

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN 'PLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC-060150

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		RECEIVED		UNIT AGREEMENT NAME	
2. NAME OF OPERATOR <i>Pan American Petroleum Corp.</i>		DEC 9 1965		8. FARM OR LEASE NAME <i>HARGRAVE-FEDERAL</i>	
3. ADDRESS OF OPERATOR <i>Box 68, Hobbs, N. M. 88240</i>		D. C. C.		9. WELL NO. <i>3</i>	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <i>510' FSL X 660' FWL, Sec 10 (UNIT M, SW/4 SW/4)</i>		MEXICO OFFICE		10. FIELD AND POOL, OR WILDCAT <i>PCA (YATES)</i>	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) <i>3210' D.F.</i>		12. COUNTY OR PARISH <i>EDDY</i>	
				13. STATE <i>N. M.</i>	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Proposal to P & A submitted on 5/4/65 and provisional approval by USGS on May 7, 1965. Provisions and hole conditions necessitated abandonment as follows:

6/23 & 24/65 Rigging up to abandon and preparing hole..

6/25/65 Spotted 32 sx plug from 1608-1270'. Shot 5-1/2" casing at 680' and lifted 11" and stuck.

6/26/65 Cemented down 5-1/2" from 680-0' with 150 sx and circulated annulus spacer between 5-1/2" and 7". Cemented outside 7", through tubing landed @ 31' with 40 sx. Then added 40-50 sx back inside 5-1/2". Filled cellar with surplus cement. Total cement approximately 350 sx.

6/27/65 Finished filling cellar and erected P & A markers.

All cement used was Hi Early Incor mixed with saturated pond brine water. All intervals filled with brine.

Pan American's representative, M. L. Claiborne. Operations witnessed and approved by: For PCA, Mr. Paul Corbin, For USGS, Mr. R. C. Baxer, Jr.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
DEC 1965
M. L. CLAIBORNE
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side