

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

LOCATE WELL CORRECTLY

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed Neil H. Wills

Date December 4, 1956 Title owner

The summary on this page is for the condition of the well at above date.

Commenced drilling 11-27-56, 1956 Finished drilling 12-1-56, 1956

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 791 to 819 No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from 735 to 736 No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
4"		8	Metl	0271	Collar		735	735	Oil string

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
4	827	125 #1 325 #2	Halliburton "		200 sack baroid

PLUGS AND ADAPTERS

Heaving plug—Material	Length	Depth set
Adapters—Material	Size	

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

TOOLS USED

Rotary tools were used from 0 feet to 827 feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

DATES

_____, 19____

DATES **Water Input Well**

Put to producing _____, 19____

The production for the first 24 hours was barrels of fluid of which% was oil;% emulsion;% water; and% sediment. Gravity, °Bé.

The production for the first 24 hours was barrels of fluid of which% was oil;%

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

....., Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	420	420	Surface sand & shale
420	595	175	Salt
595	755	160	Anhydrite - lime - start coring (75)
755	760	5	Brown dolomite
760	765	5	Anhydrite
765	767	2	Brown dolomite
767	775	8	Anhydrite
775	785	10	Gray sand - dense
785	787	2	Brown dolomite
787	821	34	Sand (oil in cores from (31-31))
821	822	1	Dolomite
822	825	3	Sand - gr. dense
825	827	2	Dolomite

30-015-06188 - Received from PI

OGRID 153653

PROP 18883

POOL 52820

26-2357

27-

88-