

(SUBMIT IN TRIPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office SANTA FE, NEW MEXICO
Lease No. N. M. 085201
Unit EAST ROCKY ARROYO

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

DECEMBER 24, 1963

Well No. 1 is located 660 ft. from N line and 1980 ft. from W line of sec. 9

<u>SW/4 SECTION 9</u> (¼ Sec. and Sec. No.)	<u>T-21-S</u> (Twp.)	<u>R-25-E</u> (Range)	<u>NMPM</u> (Meridian)
<u>WILDCAT</u> (Field)	<u>EDDY</u> (County or Subdivision)	<u>NEW MEXICO</u> (State or Territory)	

GROUND LEVEL

The elevation of the ~~surface~~ above sea level is 3355.9 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Intention to plug and abandon well at total depth of 8,688'.

Proposed plugging procedure:

Set five cement plugs at 8,450' to 8,550'; 6950' to 7050'; 5450' to 5550'; 3950' to 4050'; 3150' to 3250'. Set a 10 sack cement plug in top of 9-5/8" casing. Weld a steel cap on casing with 4" pipe marker extending about 4' above ground level with well name and description.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company MURPHY H. BAXTERAddress 1126 VAUGHN BUILDING
MIDLAND, TEXAS 79704By W. U. SimonTitle PETROLEUM ENGINEER