State of New Mexico rergy, Minerals and Natural Resources Departi.

Form C-103
Revised 1-1-89

$\widehat{\mathbb{A}}_{\lambda}$	Form C-103 Revised 1-1-8
$N\Lambda$	

DISTRICT P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION 2040 Pacheco St.			<u>(1)</u>			
F.O. DUX 1900, FIODUS, NW 00240			WELL API NO. 30-015-10060	1			
<u>DIŞTRIÇT II</u> P.O. Drawer DD, Artesia, NM 88210	Santa Fe, NM 87505		sIndicate Type of Le				
	(0)	242526212820	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	STATE FEE			
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410			₅State Oil & Gas Lea				
CLINDRY MOTIV			V-4322				
(DO NOT USE THIS FORM FOR PROP	CES AND REPORTS ON W Posals to drill or todeepe	ELES!					
DIFFERENT RESERV	OIR. USE "APPLICATION FOR F	ERMIT ARTESIA W	rLease Name or Un	it Agreement Name /7			
1Type of Well:		-	-	Rookie State			
OIL GAS WELL	OTHER	84. 68 ¹					
Name of Operator Penwell Energy, Inc.		\$151 1101 68103	«Well No.	1			
Address of Operator			₀Pool name or Wildo				
600 N. Marienfeld, Suite 1100, Midla	and, IX 79701		Undes	ignated Bone Spring			
Unit Letter B: 150 p	Feet From The North	Line and2056	Feet From The	East Line			
Section 7	Township 22S	Range 26E	NMPM 15 s	O b / County			
	10Elevation (Show whether D		THE PERSON NAMED IN COLUMN 1	County			
3662'							
	propriate Box to Indicate I	Nature of Notice, Rep	oort, or Other [Data			
NOTICE OF INT	ENTION TO:	SUBS	SEQUENT RE	PORT OF:			
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK		ALTERING CASING			
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OF	PNS.	PLUG AND ANBANDONMENT			
PULL OR ALTER CASING	<u> </u>	CASING TEST AND CEME	INT JOB				
OTHER:		OTHER: Plugback to [Delaware Sand	ì			
12Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent detes, including estimated date of starting any proposed							
work) SEE RULE 1103.	,	To politically delically delically delically	and or starting	any proposed			
7/12/96 RIH w/CIBP & set @ 6650'.	RIH w/CIBP & set @ 3000'. F	°U, RlH w/4" csg. gun & p	erfd 4 squeeze ho	oles @ 2719' - 2720'.			
7/13/98 Set retainer @ 2698'. Pump							
csg.			. omi., wran rotan	is the surface till 9 3/0			
7/17/98 PU & RIH w/ csg. gun & perf'd. Cherry Canyon w/2 JSPF @ 2638' to 2646' (8'), 16 shots total.							
7/21/98 Frac'd Cherry Canyon perfs @ 2638' - 2646' vua 2 7/8" tbg w/ 23,058 gals. Delta frac. 25 carrying 51,000# 16-30 mesh brown sand.							
I homeby and if the the Letter of				· · · · · · · · · · · · · · · · · · ·			
I hereby certify that the information above is true	and complete to the best of my knowle	edge and belief.					
SIGNATURE JUNDA ULL	uper .	Regulatory Analyst		DATE 10-21-98			
TYPE OR PRINT NAME			<u> </u>	тецерноме по. 915-683-2534			

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM DISTRICT II SUPERVISOR

APPROVED BY

DATE 10-76-78