

Land Office **New Mexico**  
Lease No. **44-06953**  
Unit \_\_\_\_\_

COPY TO (SUBMIT IN TRIPLICATE)  
**UNITED STATES**  
**DEPARTMENT OF THE INTERIOR**  
**GEOLOGICAL SURVEY**

RECEIVED

FEB 17 1964

**SUNDRY NOTICES AND REPORTS ON WELLS**

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	<input type="checkbox"/>	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL	<input type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

**February 13**, 19 **64**

**Federal "CJ" Lease**

Well No. **1-35** is located **1650** ft. from **N** line and **1650** ft. from **W** line of sec. **35**

**SE 1/4** **Sec. 35** **21S** **23E** **N.M.P.M.**  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**Indian Basin** **Eddy** **New Mexico**  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **3972** ft.

**DETAILS OF WORK**

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill a Cisco-Canyon test to an approximate total depth of 7650 feet.

A hammer drill or spudger will be used to a depth of 100 feet, 13 3/8" casing will be run and cemented with a sufficient amount to circulate. Rotary will be used from about 100 feet.

9 5/8" casing will be run to an approximate depth of 3200 feet, through the 1st Rose Springs sand, and cemented with a sufficient amount to circulate. The production string, 7" casing, will be run to approximately 7650 feet and cemented with 300 sacks.

All casing run and cemented will conform to methods approved by the U.S.G.S.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **John H. Trigg**  
Address **P. O. Box 520**  
**Roswell, New Mexico**

By *John H. Trigg*  
Title **Owner**