

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

OXY USA Inc.

16696

3. Address and Telephone No.

P.O. Box 50250 Midland, TX 79710 915-685-5717

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

810 FNL 1780 FWL NENW (C) Sec 14 T20S R28E

5. Lease Designation and Serial No.

NM0541580 - SW985

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Government T Com  
008618

8. Well Name and No.

1

9. API Well No.

30-015-20958

10. Field and Pool, or Exploratory Area

North Burton Flats 973520  
Wolfcamp Gas Pool

11. County or Parish, State

Eddy NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

Perf Add'l Wolfcamp & Acidize

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

See other side

RECEIVED

NOV 22 1995

OIL CON. DIV.  
DIST 2

PTA Morrow  
9-26-95

14. I hereby certify that the foregoing is true and correct

Signed David Stewart Title Regulatory Analyst

Date 11/20/95

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_  
Conditions of approval, if any:

ATTACHMENT 3160-5  
 OXY USA INC.  
 GOVERNMENT T #1  
 SEC 14 T20S R28E  
 EDDY COUNTY, NM

TD - 11500'      PBDT - 10885'      PERFS - 9206-9335'

MIRU PU 9/26/95, ND WH, NU BOP, PUMP 2% KCL TO KILL WELL. RIH W/ BLK PLG & SET IN PROFILE @ 10982', POOH, TEST TO 500#, HELD OK. RIH W/ STRING SHOT & BACK OFF TBG @ 10920', POOH, TOF @ 10920'. RIH W/ DUMP BAILER & DUMP 8sx CMT ON PKR & TBG, toc @ 10885'. PERF ADD'L WOLFCAMP W/ 3 JSPF @ 9294-98, 9311-19, 9331-9335', TOTAL 51 HOLES. RIH W/ PKR & 2-7/8" TBG & SET PKR @ 9127', TEST CSG TO 500#, OK. SITP-520#, OPEN WLL TO PIT, REC TRACE OIL, 0-BW, BURN 2' FLARE. 38HR SITP-920#, ACIDIZE W/ 3000gal 15% NEFE HCL ACID FOAMED W/ 1000 SCF/BBL N2, ISIP 4185#. FLOW WELL BACK 12hrs FOR 30-BO 92-BW @ 540#-FTP. RU PRO WELL TESTING, RDPV 10/3/95 & FLOW TEST WELL AS FOLLOWS:

| <u>TEST</u> | <u>FTP</u> | <u>OIL</u> | <u>WATER</u> | <u>GAS</u> | <u>CHOKE</u> |
|-------------|------------|------------|--------------|------------|--------------|
| 16HRS       | 620        | 103        | 110          | 771        | 24/64        |
| 24HRS       | 640        | 128        | 64           | 720        | 24/64        |
| 24HRS       | 430        | 137        | 57           | 705        | 24/64        |
| 24HRS       | 540        | 100        | 20           | 400        | 15/64        |
| 24HRS       | 500        | 96         | 20           | 596        | 15/64        |
| 24HRS       | 585        | 132        | 28           | 585        | 15/64        |
| 24HRS       | 500        | 85         | 21           | 585        | 15/64        |
| 24HRS       | 480        | 110        | 18           | 700        | 15/64        |
| 24HRS       | 440        | 103        | 20           | 694        | 15/64        |
| 24HRS       | 400        | 92         | 19           | 478        | 17/64        |
| 24HRS       | 420        | 71         | 10           | 650        | 18/64        |
| 24HRS       | 390        | 79         | 15           | 476        | 18/64        |
| 24HRS       | 350        | 75         | 12           | 625        | 18/64        |
| 24HRS       | 320        | 86         | 13           | 601        | 18/64        |
| 24HRS       | 290        | 65         | 12           | 593        | 20/64        |
| 24HRS       | 285        | 98         | 13           | 583        | 20/64        |
| 24HRS       | 280        | 80         | 25           | 574        | 20/64        |
| 24HRS       | 200        | 51         | 15           | 622        | 25/64        |
| 24HRS       | 260        | 86         | 23           | 574        | 25/64        |
| 24HRS       | 180        | 70         | 13           | 574        | 25/64        |
| 17HRS       | 260        | 18         | 7            | 353        | 25/64        |
| 24HRS       | 180        | 90         | 13           | 547        | 25/64        |
| 24HRS       | 160        | 73         | 10           | 502        | 25/64        |
| 24HRS       | 125        | 51         | 20           | 554        | 25/64        |

NMOCD POTENTIAL TEST 10/30/95

|       |          |          |    |     |       |
|-------|----------|----------|----|-----|-------|
| 24HRS | 125      | 70       | 12 | 516 | 30/64 |
|       | 37.2 API | 7371-GOR |    |     |       |