Form 9-331 (May 1963)

ACTING DISTRICT ENGINEER

UN D STATES SUBMIT IN TRIPLE TENTED TO THE INTERIOR VETS (Other instructions re-

Form approved.
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.

GEOLOGICAL SURVEY					o. mass. resignation and selling No.
					E L LECTRA
		AND REPO		N WELLS It of a different reservoir. Sposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAM
OIL GAS WELL WELL .	OTHER		1974	KECEIVE	7. UNIT AGREEMENT NAME
				JUL 11 1974	8. FARM OR LEASE NAME
Vates Drilli Address of Operator 207 do 4+5 S		0. 0.	C. अस्ट्रिह्	U.S. GEOLOGICAL SURV	EY 9. WELL NO.
LOCATION OF WELL (Repor				-	10. FIELD AND POOL, OR WILDCAT
See also space 17 below.) At surface 040' FSL & 1980' FLL of Sec. 35-20%S-21D					Villocat
940 * giz	मा १४ मा १६०	. Err oi a	·cc.	35-20½S-2±11	11. SEC., T., R., M., OR BLK, AND SURVEY OR AREA
PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)					Unit C Marie
		4530 ° Cit			1,400 - 1,4
6. (heck Appropr			ature of Notice, Report, c	· · · · · · · · · · · · · · · · · · ·
	E OF INTENTION TO		icare 14		SEQUENT REPORT OF:
Г	_	_	٦ :		
TEST WATER SHUT-OFF FRACTURE TREAT		LE COMPLETE		WATER SHUT-OFF FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDO		-	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANGE	PLANS		(Other) Soud ro	
(Other)				(Note: Report res Completion or Rec	sults of multiple completion on Well ompletion Report and Log form.)
nent to this work.) *	is directionally o	irilied, give subsurf	ace locati	details, and give pertinent decorated and true venues and true venues to $12\frac{1}{4}$ " at 9	ates, including estimated date of starting artical depths for all markers and zones per :30 73: 6-77-76.
		_		÷ .	
				casing set at l	
934 & 1505',	baskets :	at 988 &]	L244'	and 1-Guide sh	ide. Cemented 1/1810
_					PD 1:45 75. 751-74.
	-	_		-	00'. Rubber plug at
					PM 7-1-740.7 WOO 5 hr
& tagged cmt	at 650'.	Spotted	25 s	x of 4% CaCl.	PD 5:45 PH 7-1-74.
					% CaCl. PD-9:45 PM
					25 sx⁻²% c ac1 at:588
					1 drums of gravel.
					: 4821. 3 WOC, 3. hrs. &
					illed hale to surface
					rs. Nippled up,
installed BO	's and t	ested casi	ing t	o 1500#. OK. D	rilled shoe and teste
to 500#,0K.	Reduced :	hole to 7.	-7/8"	and resumed dr	illing. Notal sk of
cement used :	L050 sx.				三十二 人名塞纳勒勒 重人 表示人员
3. I hereby certify that the	oregoing is true	and correct			
SIGNED	Chiasi -	T ITI	LE	Engineer	DATE
(This space for Rederal o	State office use)				
APPROVED AN IET) (TITI	UE:		DATE
OND PROUS OF APPRO	VAL, F ANY:	XIII			
	1				i i i i i i i i i i i i i i i i i i i

*See Instructions on Reverse Side