Form 9-331 Dec. 1973

Drawer DD Artesia, NM 88210 0155

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

		Form Approved. Budget Bureau No. 42-R1424			
ĺ	5.	LEASE			
		NM-01119			
	6.	IF INDIAN, ALLOTTEE OR TRIBE NAME			
	7.	UNIT AGREEMENT NAME			
	8. FARM OR LEASE NAME				
١		Yates Federal C			
١	9.	WELL NO.			
1		3			
١	10.	FIELD OR WILDCAT NAME			
1		Undesignated Burton Flat Delaw			
۱	11.	SEC., T., R., M., OR BLK. AND SURVEY OR			
1		AREA			
١		Sec. 31, T20S, R28E			
١	12.	COUNTY OR PARISH 13. STATE			
ı		Eddy New Mexico			
	14.	API NO.			
-1	15	ELEVATIONS (OURW DE VER AND ME			

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME	
1. oil gas other OCT 2 6 1982	Yates Federal C 9. WELL NO.	
2 NAME OF OPERATOR	3. WELL NO.	
Exxon Corporation O. C. D.	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR ARTESIA, OFFICE	Undesignated Burton Flat Delaware	
P. O. Box 1600, Midland, Texas 79702	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec. 31, T20S, R28E	
AT SURFACE: 660' FNL & 1980' FEL of Section	12. COUNTY OR PARISH 13. STATE	
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Eddy New Mexico	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	14. API NO.	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) Later	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF		
SHOOT OR ACIDIZE		
REPAIR WELL	(NOTE: Report results of multiple completion or zone	
MULTIPLE COMPLETE	change of #orm 9–330.)	
CHANGE ZONES	1002	
ABANDON*	not 9 2 1982	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent	rectionally drilled, give subsurface locations and	
Drilled 7 7/8" hole to 4700' TD.		

Ran 111 jts 5 1/2 14# K-55 csg set at 4702'. Cmt w/250 sx C1 "C" wt. 12.11, 12 % gel, 1/4# flo-seal/sx. tailed w/800 sx C1 "C" wt. 14.8, 1/4 # flo-seal/sx Bump plug at 1:30 a.m. 10-1-82. Cmt did not circ. WOC

Ran temp survey - TOC at 1730'. Tested 5 1/2" csg 10-6-82 w/1500 Held OK

Preparing to perf.

Subsurface Safety Valve: Manu. and Type	Set @	Ft.
18. I hereby certify that the foregoing is true and correct		
SIGNED TITLE Sr. Administrator D.	October 20, 1982	
(ORIG. SGD.) DAVID R. GLASS	DATE	
U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO		