

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

Page

FIELD REPORT FOR CEMENTING OF WELLS

Operator TXC PROD CO.		Lease CAL-MON ST. COM		Well # 1	
Location of Well	Unit P	Section 7	Township 21S	Range 26E	County Eddy
Drilling Contractor WHARTON	Type of Equipment ROTARY				

* WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2"	13 3/8"	48#	NEW	525'	Circ
* 12 1/4"	8 5/8"	24#	"	2250'	Circ
7 7/8"	4 1/2"	11.6	"	10,800	700 Sxs.

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required _____

Type of Shoe used Grade Float collar used Adipill Btm 3 jts welded Yes

TD of hole 2250 Set 2251 Feet of 8 5/8" Inch 24 # Grade K-55

(New) used csg. @ 2250 with 200 sacks neat cement around shoe C.C., 2% CaCl₂
+ 200 sax TAICSE additives 10# Gils, 2% CaCl₂, ~~10# Gils, 2% CaCl₂~~ + 200 Sxs. this set, 10# Gils, ~~10#~~

Plug down @ 11:30 (AM) (PM) Date 3/25/83

Cement circulated Yes No. of Sacks 465

Cemented by HALLIBURTON Witnessed by Randy Brooks

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: + 700 Sxs. Halli life. 1# Floate, 10# Gibonite.