

MINERAL OIL COMMISSION  
Draper DD  
UNITED STATES 88210  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

0127  
Form Approved.  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well (Amended procedure, original other May 2, 1984)
2. NAME OF OPERATOR  
Discovery Operating, Inc.
3. ADDRESS OF OPERATOR  
800 N. Marientfeld, Ste. 100, Midland, TX 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1650' FSL & 1650' FEL  
AT TOP PRGD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF  
FRACTURE TREAT  
SHOOT OR ACIDIZE  
REPAIR WELL  
PULL OR ALTER CASING  
MULTIPLE COMPLETE  
CHANGE ZONES  
ABANDON\* (Amended) ☒  
(other)

SUBSEQUENT REPORT OF:

RECEIVED BY

JUN 08 1984

O. C. D.

ARTESIA, OFFICE

5. LEASE  
NM-05699
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Walt Canyon 5 Federal
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Indian Basin Upper Penn (Gas)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 5, T-22-S, R-24-#
12. COUNTY OR PARISH 13. STATE  
Eddy N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4286.5' FL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

to surface  
13 3/8" casing @ 310', cement circulated. 8 5/8" casing @ 2550', cement circulated. 4 1/2" casing @ 8005', TOC approx. 7400'. TD = 8010'. Cast Iron Bridge Plug @ 7996' with 10' cement on top. Perfs from 7938' to 7976'. Move in and rig up pulling unit. Trip out of hole with tubing. Move in and rig up wireline. Set 4 1/2" Cast Iron Bridge Plug @ 7850'. Bail 35' cement on Cast Iron Bridge Plug. Release casing and stretch to evaluate free point. Cut casing and pull (Approx. 7000') Trip in hole with tubing and spot 30 sx plug 1/2 in and 1/2 out of 4 1/2" casing stub. - Tag Spot 30 sx cement plug at 4000'. Spot 30 sx cement plug at 2600'. Spot 95 sx cement plug at 360'. Weld on cap, set dry hole marker. Cut deadmen, and clean location. Rig down and move off.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED M. M. Hamblit TITLE Engineer DATE May 9, 1984

(This space for Federal or State office use)

APPROVED BY R. P. Pitchsky TITLE P.E. DATE 6/7/84

CONDITIONS OF APPROVAL, IF ANY: