

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator MWJ PROD. CO.		Lease ST. GW com		Well # 2	
Location of Well	Unit J	Section 36	Township 20S	Range 27E	County EDDY
Drilling Contractor	Tri Serv.		Type of Equipment Rotary		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2"	13 3/8"	54.5#	new	500'	circ
* 11 1/4"	8 5/8"	32. #	"	2400'	crc
17 7/8"	5 1/2'	15.5 # 17#	"	4900'	400

Casing Data:

Surface _____ joints of 8 7/8 inch 28 # Grade J-55

(Approved) (Rejected) _____

Inspected by B. Weaver date 2-21-84

Cementing Program

Size of hole 11 1/4 Size of Casing 8 5/8 Sacks cement required 200

Type of Shoe used Tex Pat Float collar used T. Insert Btm 3 jts welded yes

TD of hole 2400 Set 2406 Feet of 8 7/8 Inch 28 # Grade J-55

New-used csg. @ 2406 with 200 sacks neat cement around shoe

+ 850 SX sax Hawco lite additives + 200 SX Hawco Thick Set

Plug down @ 645 (AM) (PM) Date 2-22-84

Cement circulated yes No. of Sacks 700

Cemented by Hawco Witnessed by B. Weaver

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: Loss zones @ 105, 865, 1025, 1574