Form 9-331 C (May 1963)

P. O. 6UX 1980

HOBBENNEW DIESTATE E88240

Form approved. Budget Bureau No. 42-R1425.

(Other instructions on reverse side) DEPARTMENT OF THE INTERIOR

JAN 20 1984

٥.	LEASI	E [)ES	16	NATION	AND	SERIA
		_	_	_			

GEOLOGICAL SURVEY								01165	
APPLICATION	FOR PERMIT T	O DRILL, D	DEEPE	N, OR	PLUG B	ACK	İ	INDIAN, ALLOTTER	OR TRIBE NAME
1a. TYPE OF WORK		DEEPEN [1	PLUG BAC	EAL WEIVE	7. UN	IT AGREEMENT N	AME
b. TYPE OF WELL OIL GA	S OTHER		S1: Z0	NGLE	MULTIP ZONE	LE		M OR LEASE NAI	
2. NAME OF OPERATOR	eum Corporat	ion			RECEIVE	O SY		LL NO.	"BC" Federal
3. ADDRESS OF OPERATOR	edit corporate						5		
207 S 4+h.	Artesia, New	Mexico	8821	0	MAR 09	1984	1	ELD AND POOL, O	
4. LOCATION OF WELL (Re	port location clearly and	in accordance wit	th any S	tate require	ements.*)	X	Eas	t Burton	Flats/Morro
At surface 990 FS	L and 1980'	FEL	. ^	1	O . C.	D . '	11. SI	EC., T., R., M., OR I	BLK. R ea
At proposed prod. zone		1.	I,U	1	ARTESIA,	OFFICE			
same	:	•		-				17-T20	
14. DISTANCE IN MILES A	ND DIRECTION FROM NEAR	REST TOWN OR POS	T OFFICE	•			12. cc	UNTY OR PARISH	13. STATE
13 miles NE	of Carlsbad.	New Mexi	co.				Edd	ly	NM
LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT.				. OF ACRES	F ACRES IN LEASE 17. NO. OF ACRES ASSIGNED TO THIS WELL 320				
(Also to nearest drlg. unit line, if any) 18. DISTANCE FROM PROPOSED LOCATION*			19. PROPOSED DEPTH 29. ROTA			RY OR C	ABLE TOOLS		
ma Michigan Well Belli INC COMPLETED.				. 120	12000' Rotar				
21. ELEVATIONS (Show whe			11				22.	APPROX. DATE WO	OBK WILL START
3291' GL								ASAP	
23.	I	PROPOSED CASI	NG ANI	CEMENT	ING PROGR	AM			
SIZE OF HOLE SIZE OF CASING WEIGHT PER FO		COOT SETTING DEPTH			QUANTITY OF CEMENT				
17 1/2" 13 3/8" 54# J-55				appr.	ppr. 640' 650 sx circulate		9		
17 1/2" 13 3/8" 34# J=33 12 1/4"-11" 9 5/8" 32# J=55				appr.		1750	1750 sx circulate		
7 7/8"	5 1/2"	17-20#			TD	250		No	at a popul

Propose to drill and test the Morrow and intermediate horizons. Approximately 640' of surface casing will be set to shut off caving and intermediate casing will be set below the Glorieta Sand. If commercial, will run 4 1/2" or 5 1/2" casing and cement with at least of Conguelle est to top of Salt Rec BIM CC. 600' cover. Su

FW gel/LCM to 1800', water to 4600', starch-drispak-KCL MUD PROGRAM: to 7600', flosal/drispak/KCL to TD.

BOP's and hydril on 9 5/8" casing, pipe rams tested daily, BOP PROGRAM: blind rams on trips, Yellow Jacket prior to drilling Wlofcamp.

Unorthodox Location GAS NOT DEDICATED. NOTE: IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposed is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout

preventer program, if any.	7) ii		
SIGNED U hat	un Koling	Regulatory Agent	DATE 1/16/84
(This space for Federal or	r State office use)		

PERMIT NO.	APPROVAL DATE	4004
S/Richard Bastin	Associate District Manager	MAR 0 6 1984
APPROVED BY	_ TITLE	
CONDITIONS OF APPROVAL, IF ANY:		APPROVAL SURJECT TO

GENERAL REQUIREMENTS AND SPECIAL STIPULATION ATTACHED

10-104/BR

MAR 7 1984

.

the second of the second

The state of the s