

45F

RECEIVED BY

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Alamosa, NM 88210

NOV 29 1984 SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. O.C.D.

ALAMOSA OFFICE

OTHER

2. NAME OF OPERATOR

Liberty Oil & Gas Corporation

3. ADDRESS OF OPERATOR

1776 Woodstead Court, Suite 200, The Woodlands, Texas 77380

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)
At surface

1875' FSL & 1765' FWL NE/4 SW/4

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3261' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM-17103

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Lee Federal

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Wildcat-Delaware

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 25, T20S, R28E

12. COUNTY OR PARISH

Eddy

13. STATE
N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☒

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

9/21/84 Perforated 5610-24'(4 SPF). Acidized with 2000 gallons of 15% HCL acid.

9/25/84 Fraced perfs with 33,000# 20/40 sand, with 20,000 gallons of CO₂ plus 7,000 gallons gel pad. Had slight show of gas.

11/01/84 Perforated 6090-92, 6120-24, 6136-40, 6164-70(1 SPF). Acidized with 2000 gallons of 15% HCL acid. No show of oil or gas.

11/06/84 Set C.I.B.P. @ 6070'. Capped bridge plug with 32' of cement. Perforated 5938-44, 5960-66, 5972-74, 5980-84(1SPF). Acidized with 2000 gallons of 15% HCL acid. Had slight show of gas.

11/13/84 Set C.I.B.P. @ 5592'. Capped bridge plug with 34' of cement.

11/14/84 Perforated 5455-91(2 SPF). Acidized with 2500 gallons of 7 1/2% acid. Fraced with 70 Quality Methanol Foam using 500 gallons of methanol, 624,000 SCF of nitrogen, 318 sx 20/40 sand, 238 sx 10/20 sand.

Testing well.

18. I hereby certify that the foregoing is true and correct

SIGNED

Terry W. Franklin

TITLE

Agent

DATE

11/27/84

This space for Federal or State office use

APPROVED BY

AWQ

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY

NOV 28 1984

Carlsbad

*See Instructions on Reverse Side

NEW MEXICO