

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE  
(Other instructions  
verse side)

Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 03364

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Big Eddy Unit

8. FARM OR LEASE NAME

Big Eddy Federal Unit

9. WELL NO.

115

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 21, T-21-S, R-29-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT-" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Bettis, Boyle & Stovall

3. ADDRESS OF OPERATOR

P. O. Box 1240, Graham, Texas 76046

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1650' FNL & 1980' FE1

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3389' GR

ARRESIA, OFFICE

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Notification of Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

The above captioned well was spudded on May 30, 1990. A twelve and one-quarter inch hole was drilled to a depth of 525' K.B. on May 30, 1990. Eight and five-eighths inch casing was then run and cemented in place as follows:

ITEM (BOTTOM TO TOP)	LENGTH	TOP of SECTION -K.B.
1 - Howco Texas Pattern Guide Shoe	0.90'	520.33' K.B.
1 - Joint, 8-5/8" 24.#/ft., J-55 ST&C	43.16'	477.17' K.B.
1 - Halliburton insert Float Collar	---	477.17' K.B.
11 - Joints 8-5/8" 24.#/ft., J-55, ST&C	471.67'	5.50' K.B.
12 - Total Casing	515.73'	
K.B. to G.L.	5.50'	
Casing set at	521.23'	

NOTE: Ran four springbow type Centralizers from 490' - 260'.

The hole was circulated for 30 minutes and cemented as follows:

-See Reverse side-

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE NEW MEXICO

\*See Instructions on Reverse Side

Pumped 10 barrels fresh water.

Cemented with 325 sacks Premium Plus, with 2% CACL<sub>2</sub> (1.32 cu.ft./sk., yield, 14.8#/gallon weight).

Displaced with 31 barrels fresh water.

Landed plug at 7:30 AM May 31, 1990.

Circulated 120 sacks cement to surface.

Waited on cement for 24 hours.

Tested to 2000 psig, held O.K.