Operator fate	Leake Jank "AIS" St				Well #3			
Location of Well	Unit <b>N</b>	Section 36		Townsh	ip	Range 31	County	
Drilling Contractor Undesignated  Type of Equipment Rotary								
* Witness								
Size of Hole	Size	of Casing	Weigh Foo		Nev	v or Used	Depth	Sacks Cement
17/2	* )	3 3/8		. 4#			850	850 Circ
1214	*	8 5/8	32	0#			4.500	2500 Circ
77/8	۷.	+ 1/2	1740	10#			TD	As Warranted
Casing Data:								
Surface joints of 8%%" inch 32 # Grade 3.55								
Inspected by								
Inspected by m.s. date 1.3/.9/								
Cementing Program								
Size of hole 12'/4" Size of Casing 85/8" Sacks coment required								
Type of Shoe used wide Float collar used insert Btm 3 jts welded ves								
TD of hole 4430' Set 4430' Feet of 856 Inch 72 # Grade 5-55  New-used csg. @ 4430' with 200 170cc sacks neat cement around shoe								
+ 1800 sax paceseffer Lite additives 670 gel. 10 # 54 LT								
ring down @ 10:45 (AM) (PM) Date 2-1-91								
Cement circulated <u>Yes</u> No. of Sacks 282								
Cemented by Western Company Witnessed by mike Stubble fiell								
Temp. Survey ran @ (AM) (PM) Date top cement @								
Casing test @ (ANI) (PNI) Date								
Method Used Witnessed by								
Checked for shut off @ (AM) (PM) Date								
Method used Witnessed by								
Remarks:								
· · · · · · · · · · · · · · · · · · ·		······································		<del></del>	<del></del>			