| Form 3160-5<br>(November 1983)<br>(Formerly 9-331) |
|--|
|  |

ADD

14. PERMIT NO.

16.

## UNITED TATES (Other DEPARTMENT OF THE INTERIOR verse side)

BUREAU OF LAND MANAGEMENT

3824.4 GR

SUBMIT IN TRIPLICAT instructions on

Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985

| 5. | LEASE | DESIG | KOITAK | AND | SERIAL | N |
|----|-------|-------|--------|-----|--------|---|
|    |       |       |        |     |        |   |

12. COUNTY OR PARISE | 13. STATE

N.M.

Eddv

| N | 1 - | 34247 |  |
|---|-----|-------|--|
|---|-----|-------|--|

|   |                                      | NII - 34247   |
|---|--------------------------------------|---|
| SUNDRY NOTICES AND REPORTS ON (Do not use this form for proposals to drill or to deepen or plug back to use "APPLICATION FOR PERMIT—" for such proposals. | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |   |
| L GAS OTHER   | RECEIVED                             | 7. UNIT AGREEMENT NAME                              |
| Collins & Ware Inc.   | JAN 3 1 1992                         | 8. FARM OR LEASE NAME Sheep Draw Federal Comm       |
| 303 W. Wall, Suite 2200 Midland, TX 79701   | O. C. D.                             | 9. WELL NO.   |
| ATION OF WELL (Report location clearly and in accordance with any State also space 17 below.) surface   | requirements.*                       | 10. FIELD AND POOL, OR WILDCAT Happy Valley Morrow  |
| 660' FNL & 2310" FEL of Sec. 33   |                                      | 11. SEC., T., E., M., OR BLK. AND<br>SURVEY OR AREA |
| MIT NO. 15 ELEVATIONS I Short inhather DE DE  |                                      | Sec. 33, T-22-S, R-26-E                             |

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO : TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL FRACTURE TREAT FRACTURE TREATMENT ALTERING CASING SHOOT OR ACIDIZE ABANDONS SHOOTING OR ACIDIZING ABANDONMENT REPAIR WELL Second intermediate casing (Norz: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other)

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any nent to this work.) \*

An eight and one half inch hole was drilled to 10,749' K.B. on January 6, 1992. Seven inch 32# &29#/ft., N-80 and RS-90 LT&C and seal lock, Casing set at . 10,742' K.B.; Float shoe at 10,740.72' K.B.; Float collar at 10,660.37' K.B.; External casing packer at 5,280.46' K.B., D.V. tool at 5,236.92' K.B. Cemented with 460 sacks Howco light premium cement with 5# gilsonite/sk., 6# salt/sk., 0.6% Halad 322 and 1/4# flocele/sk., (1.96 cu. ft./sk. yield, 12.7#/gallon). Tailed in with 540 sacks Premium cement with 5# Silicalite/sk., 3# gilsonite/sk., 0.3% gas stop, 0.7% Halad 14, and 1/4#/sk., flocele (1.34 cu. ft./sk. yield, 15.1 #/gallon). Plug down at 3:05 A.M. January 7, 1992, circulated 130 sacks cement to surface. Circulated through D.V. tool for 6 hours. Cemented second stage with 130 sacks Howco Lite with 5# gilsonite/sk., 6# salt/sk., 0.6% Halad 322 and 1/4# flocele/sk., (1.96 cu. ft./sk., yield, 12.7#/gallon). Tailed in with 740 sacks premium plus dement with 5# gilsonite/sk., 5# Silicalite/sk., 3# salt/sk., 0.6% Halad 322 and 1/4# flocele/sk., (1445 cu. ft./sk., yield, 13.6# gallon). Plug down at 10:35 A.M. January 7, 1992. Circulated 20 sacks to surface. Waited on cement 当 hours.

|   | JAN 11992               |
|---|-------------------------|
|   | EB                      |
|   | Consedfant DATE 1/21/92 |
| (This space for Federal or State office use)      |                         |
| APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY: | DATE                    |