AM OIL WS. COMMISS Brawer

Artesia, NM

RECEIVED

86210

Form	3160-5
(June	1990)

UNITED STATES

FORM APPROVED

May 3, 1993

Collins & Ware, Inc. \ 3. Address and Telephore No. 4. Location of Well (Foodage, Sec., T. R., M., or Survey Description) 1980 'FNL & 1980 'FWL of Sec. 33, T-22-S, R-26-E Eddy, New Mexico 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandomment Casing Repair New Construction Non-Routine Fracturing Casing Repair Conversion to Injection Discrebe Proposed or Completed Operations (Clearly state all pertinent death, and give pertinent date, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depils for all markers and zones pertinent to this work.)* Capstar Drilling Co. spudded a 17-1/2" hole on March 22, 1993. The surface hole was drilled to 450' on March 24, 1993. The surface hole was drilled to 450' on March 24, 1993. The surface hole was drilled to 450' on March 24, 1993. The surface hole was drilled to 450' on March 24, 1993. Capstar Drilling Co. spudded a 17-1/2" hole on March 24, 1993. The surface hole was drilled to 450' on March 24, 1993. Capstar Drilling Co. spudded a 17-1/2" hole on march 24, 1993. The surface hole was drilled to 450' on March 24, 1993. Capstar Drilling Co. spudded a 17-1/2" hole on march 24, 1993. The surface hole was drilled to 450' on March 24, 1993. Capstar Drilling Co. spudded a 17-1/2" hole on march 24, 1993. The surface hole was drilled to 450' on March 24, 1993. Capstar Drilling Co. spudded a 17-1/2" hole on march 24, 1993. Capstar Drilling Co. spudded a 17-1/2" hole on march 24, 1993. Capstar Drilling Co. spudded a 17-1/2" hole on march 24, 1993. Capstar Drilling Co. spudded a 17-1/2" hole on march 24, 1		NT OF THE INTERIOR	Expires: March 31, 1993
SUNDAY NOTICES AND REPORTS ON WELLS SUBMIT IN TRIPLICATE SUBMIT IN TRIPLICATE SUBMIT IN TRIPLICATE SUBMIT IN TRIPLICATE 1. Type of Well	BUREAU OF	LAND MANAGEMENTLY 4 10 47 AM '93	-
Do not use this form for proposals to drill or to deepen or recking to, a different reservoir. SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation	SUNDRY NOTICES	AND REPORTS ON WELLS	
SUBMIT IN TRIPLICATE Type of Weil Case Case	Do not use this form for proposals to d	rill or to deepen or reently to a different reservoir.	6. if Indian, Allottee or Tribe Name -
1. Type of Well State Well Other State Sta	Use "APPLICATION FO	PR PERMIT—" for such proposals	
1. Type of Well	CUDM	TIN TOUR LOATE	7. If Unit or CA, Agreement Designation
Swell Gas Gottom Sheep Draw Federal No. 3		TIN TRIPLICATE "LEGET LEG	
2. Name of Operator Collins & Ware, Inc. 3. Address and Telephone No. 30.3 W. Wall, Suffee 2200, Midland, Texas 79701 (915) 687–3435 4. Location of Well (Forage, Sec., T., R., M., or Survey Description) 1980 'FNL & 1980 'FVL of Sec. 33, T-22-S, R-26-E CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent No. Recompletion No. Reconstruction No. Report of Itams No. Reconstruction No. Recons	F7 Oil ☐ Gas ☐	JUN 1 4 1993	
Collins & Ware, Inc. \ 3. Address and Telephone No. 3. Address and Telephone No. 30.5 W. Wall J., Sulfee 2200, Midland, Texas 79701 (915) 687–3435 4. Location of Well (Focose, Sec., T., R., M., or Survey Description) 1980			
3. Address and Triespones No. 303 W. Wall, Suite 2200, Midland, Texas 79701 (915) 687–3435 4. Location of Well (Pootage, Sec. T., R., M., or Survey Description) 1980' FNL & 1980' FWL of Sec. 33, T-22-S, R-26-E 11. County or Barish, State Eddy, New Mexico 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION 13. Abandonment 14. Notice of Intent 15. Subsequent Report 16. Pinal Abandonment Notice 17. Casing Repair 18. Observible Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well a directionally drilled, give substarface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Capstar Drilling Co. spudded a 17-1/2" hole on March 22, 1993. The surface hole was drilled to 450' on March 24, 1993. The surface hole was drilled to 450' on March 24, 1993. The surface bole was drilled to 450' on March 24, 1993. Cemented with 500 sacks Premium Plus Cement with 2% CACL 2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.			
303 W. Mall., Suife 2200, Midland, Texas 79701 (915) 687-3435 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1980' FNL & 1980' FWL of Sec. 33, T-22-S, R-26-E 11. Country or Parish, Stote Eddy, New Mexico 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION Abandonment Change of Plans		5005 200 Guz	1
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1980' FNL & 1980' FWL of Sec. 33, T-22-S, R-26-E Eddy, New Mexico 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Subsequent Report Final Abandonment Notice Final Abandonment Notice Altering Casing Repair Water Shut-Off Conversion to Injection Dispose Water (Non-Report audit of multiple completion on Walt (Completion and measured and true vertical depths for all markers and zones pertinent to this work.)* Capstar Drilling Co. spudded a 17-1/2" hole on March 22, 1993. The surface hole was drilled to 450' on March 24, 1993. 13-3/8" 61#/ft., K-55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gailon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.	303 W. Wall, Suite 2200, Midlan	nd, Texas 79701 (915) 687-3435	L
1980' FNL & 1980' FWL of Sec. 33, T-22-S, R-26-E Eddy, New Mexico	4. Location of Well (Footage, Sec., T., R., M., or Survey I		1
Eddy, New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Recompletion Notice of Intent Plugging Back Casing Repair Water Shut-Off Conversion to Injection Notice Report results of misliple completion en W-II Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Capstar Drilling Co. spudded a 17–1/2" hole on March 22, 1993. The surface hole was drilled to 450' on March 24, 1993. 13–3/8" 61#/ft., K-55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.			
TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans New Construction	1980' FNL & 1980' FWL of Sec. 3	33, T-22-S, R-26-E	
TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent			Eddy, New Mexico
Notice of Intent	12. CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA
Subsequent Report Recompletion Recompletion Rev Construction Recompletion Recompletio	TYPE OF SUBMISSION	TYPE OF ACTION	** · · · · · · · · · · · · · · · · · ·
Recompletion New Construction Non-Routine Fracturing Water Shut-Off Casing Repair Water Shut-Off Casing Repair Dispose Water (None: Report results) of multiple completion on well (Constitute) of Recompleted Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Capstar Drilling Co. spudded a 17–1/2" hole on March 22, 1993. The surface hole was drilled to 450' on March 24, 1993. 13–3/8" 61#/ft., K–55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.	Notice of Intent	Abandonment	Change of Plans
Capstar Drilling Co. spudded a 17-1/2" hole on March 22, 1993. The surface hole was drilled to 450' on March 24, 1993. 13-3/8" 61#/ft., K-55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.		Recompletion	
Final Abandonment Notice Altering Casing Dispose Water Note: Report results of multiple completion on Well Conversion to Injection Dispose Water (Note: Report results of multiple completion on Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Capstar Drilling Co. spudded a 17–1/2" hole on March 22, 1993. The surface hole was drilled to 450' on March 24, 1993. 13–3/8" 61#/ft., K–55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.	Subsequent Report	Plugging Back	Non-Routine Fracturing
Capstar Drilling Co. spudded a 17–1/2" hole on March 22, 1993. The surface hole was drilled to 450' on March 24, 1993. 13-3/8" 61#/ft., K-55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.		Casing Repair	Water Shut-Off
(Note: Report scatted of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Capstar Drilling Co. spudded a 17–1/2" hole on March 22, 1993. The surface hole was drilled to 450' on March 24, 1993. 13–3/8" 61#/ft., K-55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.	Final Abandonment Notice	l — — · · ·	Conversion to Injection
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Capstar Drilling Co. spudded a 17–1/2" hole on March 22, 1993. The surface hole was drilled to 450' on March 24, 1993. 13–3/8" 61#/ft., K–55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.		XXOther Surface Casing	
Capstar Drilling Co. spudded a 17–1/2" hole on March 22, 1993. The surface hole was drilled to 450' on March 24, 1993. 13–3/8" 61#/ft., K-55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.	11. D		Completion or Recompletion Report and Log form)
Capstar Drilling Co. spudded a 17–1/2" hole on March 22, 1993. The surface hole was drilled to 450' on March 24, 1993. 13–3/8" 61#/ft., K–55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.	give subsurface locations and measured and true vertice	Il pertinent details, and give pertinent dates, including estimated date of startin cal depths for all markers and zones pertinent to this work.)*	g any proposed work. If well is directionally drilled,
The surface note was drilled to 450' on March 24, 1993. 13-3/8" 61#/ft., K-55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.		, , , , , , , , , , , , , , , , , , , ,	
The surface note was drilled to 450' on March 24, 1993. 13-3/8" 61#/ft., K-55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours. **Automotion of the surface			
The surface note was drilled to 450' on March 24, 1993. 13-3/8" 61#/ft., K-55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.	•		
The surface note was drilled to 450' on March 24, 1993. 13-3/8" 61#/ft., K-55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours.			
The surface note was drilled to 450' on March 24, 1993. 13-3/8" 61#/ft., K-55 Buttress casing was run and set at 450.52' K.B. Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours. **Automotion of the surface	Capstar Drilling Co. spudded a 17-1/2"	hole on March 22 1993	
Cemented with 500 sacks Premium Plus cement with 2% CACL2 (1.32 cu.ft./sk. yield, 14.8#/gallon). Circulated 40 sacks cement to surface. Waited on cement 22 hours. **J. Jana** 1993**	The surface hole was drilled to 450' on	March 24 1993	
Circulated 40 sacks cement to surface. Waited on cement 22 hours. A Sass.	13-3/8 61#/ft., K-55 Buttress cas	IND was run and set at 450 50 V p	
A Aura 1993	Cemented with 500 sacks Premium Plu	Signment with 29 CACLO / 1 30 out the late state of	4.0 # 4
J. Jara 1993	Circulated 40 sacks cement to surface.	Waited on cement 22 hours	4.8#/gallon),
J. Aus.		The state of the s	•
J. Jara 1 1993		جمع چوري	Software and the Control of the Cont
J. Jara 1 1993			The state of the s
1993	,		J. Jara
			/ 1993
	ı		
	14. I hereby certify that the foregoing is true and correct		and the second second

(This space for Federal or State office use) Approved by ______ Conditions of approval, if any: Title Date

Agent for Collins & Ware, Inc.