<u>, 4€0</u>		<i>C</i> (7).
	TED STATES AT DIE COMMISSION	1
ine 1990)	T OF THE INTERIOR AND DES	Budget Bureau No. 1004-0135 Expires: March 31, 1993
BUREAU OF I	T OF THE INTERIOR AND MANAGEMENT	5. Lease Designation and Serial No.
SUNDRY NOTICES	AND REPORTS ON WELLS	NM 0486
Do not use this form for proposals to dr	ill or to deepen or reentry to a different reservoir.	6. If Indian, Allottee or Tribe Name
Use "APPLICATION FO	R PERMIT—" for such proposals	
SUBMIT	IN TRIPLICATE	7. If Unit or CA, Agreement Designation
. Type of Well	The second secon	
Cas C		8. Well Name and No.
Name of Operator		Garretson AMI Federal #3
YATES PETROLEUM CORPORATION	(505) 748-147 1)	9. API Well No.
3. Address and Telephone No.		30-015-27404
105 South 4th St., Artesia, NM 88210		10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec., T., R., M., or Survey D	escription)	Fenton Delaware
Unit F, 1980' FNL & 2180' FM	J. Sec. 21-T21S-R28E	11. County or Parish, State
U	3	Eddy, NM
CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
_	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	X Water Shut-Off
Final Abandonment Notice	Altering Casing X Other	Conversion to Injection
	LXJ Other	Dispose Water (Note: Report results of multiple completion on Well
	all pertinent details, and give pertinent dates, including estimated date of startin	Completion or Recompletion Report and Log form.)
Spudded 36" hole 12:10 PM 4- of spud. Resumed drilling 2 346'. Guide shoe set 346'. 1.76, 12.9). Tailed in w/25 Did not bump plug. Float hel WOC 22 hrs and 15 minutes. drilling. TD 17½" hole 9:00 Guide shoe set 1020', insert seal, 10#/sx Salt (yield 2.1 PD 3:35 PM 4-20-93. Bumped	ical depths for all markers and zones pertinent to this work.)* 13-93. Set 40' of 30" conductor pipe. 6" hole 8:10 PM 4-15-93. Ran 8 joints Insert float set 302'. Cmt'd w/460 s 0 sx "C" w/2% CaCl2 (yield 1.32, wt 14 d OK. Circulated 100 sacks. WOC. Dr Cut off and weld on flow nipple. Redu AM 4-23-93. Ran 23 joints 13-3/8" 54 float set 980'. Cmt'd w/700 sx PSL " 7, wt 13). Tailed in w/200 sx "C" w/2 plug to 400 psi, float held OK. Circu 8 hrs and 40 minutes. NU and tested to med drilling.	20" 94# H-40 casing set x PSL "C" w/2% CaCl2 (yield .8). PD 10:45 PM 4-16-93. illed out 10:00 PM 4-17-93. ced hole to 17½". Resumed .5# J-55 casing set 1020'. C" w/1% CaCl2, 1/2#/sx Cello-% CaCl2 (yield 1.32, wt 14.8) lated 210 sacks. WOC. Drill
14. I hereby certify that the foregoing (s true and correct		
signita Darollin	Title Production Supervisor	Date 5-5-93
This space for Federal or State office use)		
Approved by	Tktle	Date
Conditions of approval, it any.		
THE 10 H C C CONT 1001	on knowingly and willfully to make to any department or agency of the Unit	ed States any false, fictitious or fraudulent statements
Title 18 U.S.C. Section 1001, makes it a crime for any pers or representations as to any matter within its jurisdiction.	on knowingly and without to make to any department of agency of the Onito	ou outes any two-, monitors of fraudaton successing