1914 UIL CURS. CUMMISSION DRAWER DD

Form 3160-3 (July 1992)

(Other instructions on reverse side)

FORM APPROVED OMB NO. 1004-0136 Expires: February 28, 1995

UNITED STATES

DEPARTMENT OF THE INTERIOR						S. LEASE	5. LEASE DESIGNATION AND BERIAL NO.		
BUREAU OF LAND MANAGEMENT						NM 88115			
··· · · · · · · · · · · · · · · · · ·	CATION	FOR PE	RMIT TO	DRILL	OR DEEPEN		6. IF IND	IAN, ALLOTTEB C	R TRIBE NAME
1a. TYPE OF WORK DRI b. TYPE OF WELL	LL xxx		DEEPEN				7. דואט	AGREEMENT NAM	(B
OIL GAS WELL OTHER SINGLE ZONE ZONE					Federal				
Collins & Wa	re, Inc	. 🗸			AUG	161993	9. AH WEL	TNO	
3. ADDRESS AND TELEPHONE NO							30	- 015-27	'63Z
303 W. Wall,				79701	A PROPERTY.	L.D.	10. FIELD	AND POOL, OR	WILDCAT
4. LOCATION OF WELL (R) At surface 1980 At proposed prod. zon	' FSL &	clearly and		ith any Si	tate requirements.*)		11. SEC.,	Valley (T. B., M., OR BL SURVEY OR AREA 33, T22	K.
14. DISTANCE IN MILES	ND DIRECTIO	N FROM NEAR	EST TOWN OR PO	ST OFFICE	•		12. COUN	TY OR PARISH	13. STATE
3.9 miles SV	V of Car	lsbad, N	М				Ed	ldy	NM
15. DISTANCE FROM PROPO LOCATION TO NEAREST PROPERTY OR LEASE L (Also to Degrest drig	INE, FT.	(any)	1980'				OF ACRES ASSIGNED HIS WELL 40		
IS. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. 1320*			ı)50 1		ary	E TOOLS		
21. ELEVATIONS (Show who	ther DF, RT,	GR, etc.)	33 2! ' Gr.	Carlst	ad Controlled W	ater Basin		PROX. DATE WORD Approval	
23.]	PROPOSED CAS	SING AND	CEMENTING PROGR	AM			
SIZE OF HOLE	GRADE, SIZZ	3 OF CASING	WEIGHT PER	FOOT	SETTING DEPTH		MAUQ	TITY OF CEMENT	
17.5"	133/8	4-55	48-6D	#54	5 350'	400 sts CIRCUL		ATE	
11.0 "	85/8	J-55	24#	-	1650'	_657	osks		الماني
7.875"	5/2	4-55	15.5H	٤	50001	650	osts		
production of in a matter corengineering prare out lined 1. Well Locat 2. Drilling Fraction Exhibit 3. Surface Us	onsistantactice. in the tion and Program #1-BOP	t with F Specif followin Acreage	ederal and ic program g attachme	d Stat ms acc ents:	e regulation ording to on-	and acco shore Oi bject to direments	ording il and	to good	223 273 273 273 273
Exh. #2	2- Exist	ing Road	s		4- D. Ri	g Layout	-	€	#€ 1271
2A- Planned Access Roads 5- Prod. Fac. Lay						ayout	der one der one der one	IO.	
			us Map wit	th lea	se boundary			ت	8-20
3.6 N ABOVE SPACE DESCRIBI	- Well		mnocal is to deepen	n pive data	on present productive zor	ne and proposed	d new neodu	دت 💎	<i>AL9</i> posal is to drill o
eepen directionally, give perti									
+									
BIGNED YV CAL	بمنظيم	Max Gue	rry 1	іть є <u>Re</u>	gulatory Mana	ger		TE 7-16-93	
(This space for Feder									
PERMIT NO.					APPROVAL DATE				
Application approval does n	ot warrant or co	rtify that the appl	icant holds legal or	equitable titl	e to those rights in the subje	ct lease which w	rould entitle ti	he applicant to conc	duct operations the
CONDITIONS OF APPROVAL		_	.1						
LI	RIL	. W)	_				AUG 19	1923

*See Instructions On Reverse Side

Submit to Appropriate District Office State Lease - 4 copies Fee Lease - 3 copies

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-102 Revised 1-1-89

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410

1320 1650 1980 2310 2640

WELL LOCATION AND ACREAGE DEDICATION PLAT

1000 IGO BIZZOS RII., AZZOC, NIV	All Dis	stances must be	from the outer boundaries	s of the section	
Operator			Lease		Well No.
COLLINS & WA	RE, INC.		DALL FEDERAL		1
Unit Letter Section	Township		Range	·Co	ounty
К 3:	3 22	SOUTH	26 EAST	NMPM	EDDY COUNTY, NM
Actual Footage Location of Wei	Δ :				
1980 feet from		line and	1980	feet from the	WEST line
Ground level Elev.	Producing Formation		Pool		Dedicated Acreage:
3321. D	Delaware		Happy Vaile	y	40 Acres
1. Outline the acreage	e dedicated to the subject w	eil by colored pe	ncil or hachure marks on the	plat below.	
2. If more than one le	ease is dedicated to the wel	l, outline each and	l identify the ownership there	eof (both as to working i	nterest and royalty).
3. If more than one le	ease of different ownership	is dedicated to th	e well, have the interest of al	ll owners been consolida	ted by communitization,
unitization, force-p	•				•
Yes			pe of consolidation		
		ptions which have	actually been consolidated.	(Use reverse side of	
this form if neccessar No allowable will be	•	Il interests have h	een consolidated (by commu	initization unitization fo	amed-pooling or otherwise)
	rd unit, eliminating such int			and and an analysis, re	pooling, or outer with
			· · · · · · · · · · · · · · · · · · ·		ODED AMOD GEDTTEIGATION
			1		OPERATOR CERTIFICATION
			i	l com	I hereby certify that the information ained herein in true and complete to the
i			i		of my knowledge and belief.
			i		
			! !	Sign	atum
			i :		
			1	Pnni	led Name
<u></u>		1		Ma	ax Guerry
			1	Posi	
				Re	egulatory Mgr.
					npany
				Co	ollins & Ware, Inc.
1			1	Date	
İ			į		7-16-93
			i	==	
		_}	_		SURVEYOR CERTIFICATION
i			İ	I h	ereby certify that the well location show
					this plat was plotted from field notes of the surveys made by me or under m
1980	•			'	ervison, and that the same is true an
	Y				rect to the best of my knowledge an
		1		, beli	ef
i		-	i	Da	ie Surveyed
·i		1		1	ULY 1, 1993
			i		
J			İ	Pro	ressional Surveyor
·	980		i I		ressonal surveyor
	-		 		(()) ()
Į.					5412
			!		Export &
1		1		The second secon	ruficate No. SURTE
1					M RESPS NON 54 12
		_		N.	TO THO FEEL OF TE
0 330 660 990 132	0 1650 1980 2310	2640 20	000 1500 1000	500 0	

DRILLING PROGRAM

COLLINS & WARE, INC.

DALL FEDERAL #1

1980' FSL & 1980' FWL, UNLTR K, Sec. 33, T22S, R26E

EDDY COUNTY, NM

The following information is filed in accordance with New Mexico Oil Conservation Rules and Regulations:

1. SURFACE FORMATION: Quaternary

2. ESTIMATED TOPS OF GEOLOGIC MARKERS:

Delaware 1680' Cherry Canyon 2550' Bone Springs 4950'

3. ESTIMATED DEPTH TO FRESH WATER:

Possible fresh water 100'-300'

ANTICIPATED POSSIBLE HYDROCARBON BEARING ZONES:

Delaware (below 1700')

No other formations are anticipated to give up commercial quantities of hydrocarbons.

The fresh water sands will be protected by setting 13 3/8" casing at 350'and circulating cement back to surface. First intermediate 8 5/8" casing will be set at 1650' and cement circulated back to surface. The 5 1/2" production string will be set at 5000' and cement circulated back to surface.

4. PROPOSED CASING AND CEMENTING PROGRAM:

Casing Hole Size	Interval	Casing OD	WT., Grade, Joint, Condition
17.5"	0-350'	13 3/8"	48-61#, K-55, ST&C, New
11.0"	0-1650'	8.5/8"	24#, J-55, ST&C, New
7.875"	0-5000′	5 1/2"	15.5#,K-55,LT&C,New

Cement:

13 3/8" Surface Csg.: Cemented with 400 sacks of Class "C" with 2% CaCl. Circulate cement.

8 5/8" First Intermediate: Cemented with 425 sacks of 50-50 Pozmix cement tailed in with 225 sacks of Class "C" with 2% CaCl. Cement to circulate.

5 1/2" Prod. Csg.: Cemented with 400 sacks of Lite cement tailed in with 250 sacks of Class "C" with 1% CaCl to circulate to surface.

Page 2- Drilling Program
Collins & Ware, Inc., Dall Federal #1

5. PRESSURE CONTROL EQUIPMENT:

Blowout prevention equipment, while drilling below surface casing will be a 3000 psi working pressure BOP stack. The BOP sketch is shown as Exhibit 1.

6. CIRCULATING MEDIUM:

Surface to 500': Fresh water spud mud: viscosity 30 to 33 as required for hole cleaning, 8.5-8.8#/gal.

500' to 1650': Fresh water with lost circulation material as required, 28-30 viscosity, pH 9-10, weight 8.5-8.8#/gal.

1650'to TD: 10# brine system circulating reserve pit. Weight 9.5-10#, ph 9-10, viscosity 30-36, with mud sweeps as required. Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept at the well site at all times.

7. AUXILIARY WELL CONTROL AND MONITORING EQUIPMENT:

- A. An upper kelly cock will be used.
- B. The drilling fluids system will be visually monitored at all times.
- C. A mud-logging unit will monitor drilling penetration rate and hydrocarbon shows from somewhere below the intermediate casing. (tentative)


8. TESTING, LOGGING, AND CORING PROGRAMS:

- A. No drill stem tests are planned.
- B. Compensated Neutron/LDT Log GR and Dual Laterolog w/ MSFL. The Gamma Ray Log will be continued back to surface.
- C. Mud-logging unit will be used below 2700'.
- D. A set of sidewall cores is anticipated.
- E. Other testing procedures may be used after the production casing has been set depending on shows and other testing indicators.

9. <u>ABNORMAL CONDITIONS</u>, <u>PRESSURES</u>, <u>TEMPERATURES</u>, <u>& POTENTIAL</u> HAZARDS:

No abnormal pressures or temperatures are anticipated. The estimated bottom-hole temperature (BHT) at TD is 90F and the estimated maximum bottom hole pressure (BHP) is about 1400 psi. No hydrogen sulphide (H2S) or other hazardous fluids are known to exist at this depth and area. No lost circulation zones are anticipated.

10. ANTICIPATED STARTING DATE AND DURATION OF OPERATIONS: It is planned that operations will commence shortly after approval of this application, with drilling and completion operations lasting about 30 days. A decision as to design and installation of permanent facilities will be made after adequate testing of the well.




Blowout Preventer 3000 psi working pressure

EXHIBIT (
COLLINS & WARE, INC.

DALL FEDERAL NO. (
1980 FAL & 1980 FAL

Sec. 33, I-22-S, R-26-E

Eddy County, NM



BOP STACK

3000 PSI WORKING PRESSURE

IN USE WHILE DRILLING BELOW 8-5/8" CASING SEAT

Exhibit No. IA BOP ARRANGEMENT

SURFACE USE AND OPERATIONS PLAN

FOR

COLLINS & WARE, INC.
DALL FEDERAL #1

1980' FSL & 1980' FWL, K, Sec. 33, T22S, R26E EDDY COUNTY NM

LOCATED: 3.9 miles SW of Carlsbad, NM.

FEDERAL LEASE NUMBER: NM-88115

ACRES IN LEASE: 80

TERM: HBP

LESSEE: Collins & Ware, Inc.

SURFACE OWNERSHIP: Federal

GRAZING PERMITEE: Bill Gillock

159 Gillock Rd. Carlsbad, NM 88220

POOL: Happy Valley (Delaware)

POOL RULES: SWR: 40 acre spacing for oil.

EXHIBITS: 2. Existing roads

- 2A. Planned access roads
- One-Mile Radius Map showing lease boundary and wells
- 3A. Well Status
- 4. Drilling Rig Layout
- 5. Production Facilities Layout

Page 2 - Surface use and operations plan Collins & Ware, Dall Federal #1

1. EXISTING ROADS:

A. Exhibit #2 is a portion of a map showing the location of the proposed well as staked.

B. Exhibit #2A is a topo map showing existing pertinent roads in the vicinity of the proposed well site.

2. PLANNED ACCESS ROAD:

- A. Length and Width: The lease road to be constructed will be about 700' +- long and about 12' wide.
- B. Surfacing Material: Caliche, watered, compacted and graded.
 - C. Maximum Grade: Less than one per cent (1%).
 - D. Turnouts: None necessary.
- E. Drainage Design: Any new road will be crowned with drainage to the side.
 - F. Culverts: None needed.
 - G. Gates and Cattleguards: None will be necessary.
 - H. Cuts and Fills: Very little necessary.
- I. Existing access roads to the proposed wellsite will be used in their present state. Off-lease access approval will be executed under the DALLFED location.

3. LOCATION OF EXISTING WELLS:

A. Existing wells within a one-mile radius are shown on Exhibit #3. There are no disposal, injection, and/or observation wells.

4. LOCATION OF EXISTING AND/OR PROPOSED FACILITIES:

A. Necessary production facilities for this proposed well will be located on the well pad. A layout of the production facilities is shown in Exhibit #5.

5. LOCATION AND TYPE OF WATER SUPPLY:

A. It is not planned that a water supply well will be drilled. Water necessary for drilling operations will be purchased and trucked from commercial water stations to the well site, or will be moved to the well site by temporary pipeline laid on the ground along-side existing and proposed roads.

6. SOURCE OF CONSTRUCTION MATERIALS:

A. Caliche needed for construction work will be taken from commercial sources located in the area.

7. METHODS OF HANDLING WASTE MATERIAL:

- A. Drill cuttings will be disposed of in the drilling pits.
- B. Drilling fluids will be allowed to evaporate in the drilling pits until the pits are dry.
- C. Water produced during tests will be disposed of in the drilling pits. After the well is permanently placed on production, produced water will be collected in fiberglass or steel tanks until hauled by transport to an approved disposal system.
- D. Oil produced during tests will be stored in test tanks until sold.
- E. Trash, waste paper, garbage and junk will be stored in a covered, above-ground container. All waste material will be contained to prevent scattering by the wind. Location of the trash container is shown on Exhibit #4. No toxic waste or hazardous chemicals will be produced by this operation. The container will be emptied when full and taken to an authorized disposal facility.
- F. All trash and debris will be removed from the well site within 30 days after finishing drilling and/or completion operations. No adverse materials will be left on location. The unused portion of the well site will be leveled and restored to BLM specifications. Only that part of the pad required for production facilities will be kept in use. In the event of a dry hole, only a dry hole marker will remain.
- G. If required, a portable, chemical toilet will be provided on the location for human waste during the drilling and completion operations.

8. ANCILLARY FACILITIES:

A. No airstrip, campsite, or other facilities will be built as a result of the operations of this well.

9. WELL SITE LAYOUT:

- A. Exhibit #4 shows the relative location and dimensions of the well pad, mud pits, reserve pit, and the location and orientation of major drilling rig components. No permanent living facilities are planned, but a temporary foreman/toolpusher's trailer will be on location during the drilling and completion operations.
- B. Clearing and leveling of the well site will be required. Top soil, if available, will be stockpiled per BLM specifications as determined at the on-site inspection. No major cuts will be required.
 - C. The pad and pit area are staked and flagged.

Page 4 - Surface use and operations plan Collins & Ware, Dall Federal #1

10. PLANS FOR RESTORATION OF THE SURFACE:

- A. After completion of drilling and/or completion operations, all equipment and other material not needed for operations will be removed from the well site. The location will also be levelled and cleaned of all trash and junk, to leave the well site in an as aesthetically pleasing condition as possible. Any part of the pad not needed for production facilities will have the top soil replaced and reseeded.
 - B. Unguarded pits containing fluids, if any, will be fenced.
- C. After abandonment, all equipment, trash, and junk will be removed and the well site will be cleaned. Any special rehabilitation requirements of the surface management agency will be complied with and accomplished as rapidly as possible.

11. OTHER INFORMATION:

- A. Topography The land surface in the area is fairly level. In the immediate area of the well site, land slope is gentle down to the east.
- B. Soil Top soil at the well site is a loamy sand with some minor dune development.
- C. Flora and Fauna The vegetation cover is medium and includes mesquite, shinnery oak, sand sage, plains yucca, various weeds, and range grasses. Wildlife in the area is that typical of semi-arid desert land and includes coyotes, rabbits, rodents, reptiles, dove and quail.
- D. Ponds and streams No lakes, ponds, or streams are in the area.
- E. Residences and other structures There are no occupied dwellings or other structures, other than oil field related equipment, within a mile of the proposed well site.
- F. Archaeological, historical, and cultural sites None observed. However, an archaeological reconnaissance will be done and a report furnished.
- G. Land use Oil and gas production, grazing and wildlife habitat.
 - H. Surface ownership Federal with a grazing lease.

Page 5 - Surface use and operations plan Collins & Ware, Dall Federal #1

12.OWNER'S REPRESENTATIVE:


Max Guerry Collins & Ware, Inc. 303 W. Wall, Ste. 2200 Midland, TX 79701 Tel: 915-687-3435

13.CERTIFICATION:

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions which currently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and, that the work associated with the operations proposed herein will be performed by Collins & Ware, Inc. and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U. S. C. 1001 for the filing of a false statement.

Date: 7-16-13

Max Guerry Regulatory Manager



REVISEU CA Ac Ki 2617 BIG HORN STATE SECTION LINE \$ ZASE RAMENE #1 500 FSL 3331T 1980 FSLL 1980 (\$100) 54.33,725, Ethibir 2A SCAUE: 17-1000' . 3378 3.8991 3340 02 33961 18/2 STATE 18841 OFBARBADOS STATE 11 2 € 3375 IM "EV" STATE !! 3348T

e e : : : : : : : : : : : : : : : : : :	•			
JA2190 mary Fuels) Amoco-Fed.	Floyd Ener CarterFdi. 4M.1 8 2 83 R I. Floyd(S)	Santa Fe Ener., 1/2 HBP 34747	ች 4.8Mil.	Hackberry Hills Unit
Cony Disc.	Carter Fdn, MI. RI MAS Fed. RI Floyds	R I Floyd(S)y	"Lea"	DRAW, ME.
itchell	Hanagan Pet Yates TX0 Pet.etal 10-21 90 88114 6 1 96 Yates		Exxon 59378	Exxon R.Hink 12-1-89 56231 7 19-1
inec.	12 00 96533 Pet. efal 2.3.92 Yates Exxon Br.C.Disc UTI Ener. Pet. etal 91 TO11720 1 5.1.94 10.21.90 64578 P/84273 VX 81614	RI Floyd(S) (q.	1 Str. Disc. 5.3Mil "Happy valley.	Sings 8 23 4. 2. Gulf M. Sche 8 1 8 4 17
	21 51 2 5 2 5 2 5 1 5 1 5 1 5 1 5 1 5 1	56510 2 HBC 5/2	Happy valley Fed " Exxon Amocol 7:1 B6	13625 - 27 T.A All Exxon - Gulf
ST Not I Bak Y	RFloydetal R Floydis / Lea Co. /2 M.I. Yates	Happy Valley: Fed." Job B Amoco	11-1-86 45230 34247 136299 KG5	45229 K 675 4 4 Mil. Stat.
2 M.I. Yales Pt. 2:3:92 5:12:92	10 21. 900 Pfoll of the Peteral 19.89 2.3.92 Corter 57.512 Form M. 1. Peteral 2.3.92 Form M. 1. Peteral 2.3.92 Form M. 1. Proyaleto	0 11-1-88 0 34247 U.5.	5188 V-707 3508 State	Gulf 1 8 · 1 LA Tomaino Fedits 13625
11 - 1 - 93	Chevron Yutes Yates 5 1 90 Pet Pet Pet Pet Pet Pet Pet Pet Pet Pet	O HBP O	Mew- STMILBOURNE OZ OIL	Cit Serv Texaci HBP 31202
VB·288 64 % V	HBC 5-1-90 325 02 W/2 LG-8291 70833	34247 Colling Sheep Fee!	ns & Wart 84847 Draw 320000	(G Br. On (P)
(Exxon 5.1.90	D.F. Gonzales	3 Amoco Sonta Fe Ener., 1/2	Merit Ener. 0331649 34 PTZ (C.
CNO	*NMSt." 708 33 Chevron Exxon 5 1 80	570	. 0331649 Collins E.Ware Aam Ewe Fed	4.5Mil. DN
	16-8291 V-708 70833 State	1 U	S.	Midwest Fed y s Fed
13 51,10,18 Tates Pet.etal 4 1 96 421	30.13	÷ Exx	· •	4078 414084 112572 2 Merit Ener.
9 90 +	Yates Pet etal 9 : 1 : 93 76971 200	TO 3508 33	34 °° 55	⊢ ⊥ K-2957 - ↓ (Mi
race veva Ut.	5 Cit Serv. Fed Morrow Disc. 13 Mil	Exhibit the		3 Y Atc Mo.
r, Disc. .8 Mil. 9-4-75	Pig.li 10 82 Hillin Prod. Ciries Fed	Cities Serv State		State
Santa Fe Ener	Amoco Exxon 3 1-91 2-1-91	Ox.ex ON 5	xon Bettis Bros. 193 etal., 72 2456 Collins E Ware	Yates Par, etal (Bett
2 94 v 2838 4 45 11	39134 64581 33400 KG5	Bettis Bros. etal. 次 Collus & Ware	Ware 12 (-93 V 2767 50 99	ジ・オミラの Vintage 「 5920 to 12,0 K 453
st	8	12 · 1 · 93 V· 2767 50 <u>90</u>)	Hamon St. K-4400 TO 1012000

EXHIBIT NO. 3A STATUS OF WELLS WITHIN ONE-MILE RADIUS COLLINS & WARE, INC. DALL FEDERAL #1 WELL SECTION 33, T-22-S, R-26-E, EDDY COUNTY, NEW MEXICO

T-22-S, R-26-E

SECTION 28

Collins & Ware, Inc. Happy Valley "B" Fed. #1, 11692' TD, 1471' FSL & 1908' FWL, Morrow Prod.

SECTION 32

Collins & Ware, Inc. "EV" State Com., 11788' TD, 1980' FWL & 1980' FSL, Strawn Prod.

SECTION 33

Collins & Ware, Inc. Sheep Draw #1, 11735' TD, 660' FNL & 2310' FEL, Strawn Prod.

Collins & Ware, Inc. Sheep Draw #2, 4990' TD, 990' FNL & 2310' FWL, Delaware Prod.

Collins & Ware, Inc. Sheep Draw #3, 5000' TD, 1980' FNL & 1980' FWL, Delaware Prod.


SECTION 34

Merit Energy Midwest "L" Fed. Com. #1, 11856' TD, 1980' FWL & 1850' FSL, Strawn Prod.

T-23-S, R-26-E

SECTION 4

Union Federal #1, 3508' TD, 660' FWL & 660' FNL, Dry Hole






EXHIBIT # 5
PRODUCTION FACILITIES LAYOUT
DALL Federal No. 1

Scale: None