

45F

Form 3160-5  
 (June 1990)

UNITED STATES  
 DEPARTMENT OF THE INTERIOR  
 BUREAU OF LAND MANAGEMENT

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
 Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

FORM APPROVED  
 Budget Bureau No. 1004-0135  
 Expires: March 31, 1993

5. Lease Designation and Serial No.

*NM-89805*

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

*NMNM 91028X*

8. Well Name and No.

*MCGANDER HILL 12 FEU Unit #1*

9. API Well No.

*30-05-27918*

10. Field and Pool, or Exploratory Area

*UNDESIGNATED (NMAW)*

11. County or Parish, State

*EDDY CO, NM*

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

*YATES ENERGY CORPORATION*

3. Address and Telephone No.

*P.O. BOX 2323 ROSWELL, NM 88202 905-623-9935*

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

*330' FWL @ 1680' FSL*

*SEC 12 - T22S - R25E*

**12 CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other *RUN CASING*  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

*10/22/94 TO WELL @ 11,220'. RAN 5 1/2", 15.5" + 17", N-80 + R-55  
 CHANG TO 11,216', FLOAT COLLAR @ 11,139', DV TOOL @ 80.14'.  
 CEMENT 1ST STAGE W/ 20 BBLs FW, 1000 GALS SUPERFUSN, 725 SX  
 PREMIUM PLUS W/ 0.37% HALAD 322, 0.4% HALAD 344 + 5# KCI  
 @ 15.6 PAG, 1.24 FE<sup>3</sup>/SX. BUAP PLUG, FLOAT HEAD. OPEN DV  
 TOOL + OAC 6 HRS. CEMENT 2ND STAGE W/ 900 SX LITE PREMIUM  
 PLUS, 1/4" FROCELE + 5# NACI. @ 12.6 PAG, 2.0 FE<sup>3</sup>/SX. TAILED  
 IN W/ 100 SX PREMIUM PLUS NEAT. TOX CALCULATED @ 2136'.  
 SET SLIPS, CUT OFF CSG + INSTALLED 11"-3M x 7 1/4"-5M TBG  
 HEAD. RELEASED RIG @ 10:30 AM 10/22/94. BLM NOTIFIED  
 BUT DID NOT WITNESS.*

14. I hereby certify that the foregoing is true and correct

Signed

Title

*ENGINEER*

Date

*10/25/94*

(This space for Federal or State office use)

Approved by

Title

Date

*1994*

Conditions of approval if any:

*JU*