NM OIL CONS COMMISSION Drawer DD Artesia, NM 88210

Form 3160-5 (June 1990)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Burn	eau No.	1004-0135
Expires:	March	31, 1993

	30112110 01	EINID MANAGEME	14.1		5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.			:	NM-81219	
			it reservoir	6. If Indian, Allottee or Tribe Name	
	Use "APPLICATION FO	OR PERMIT—" for suc	on proposals	t reservoir.	
	SURMI	T IN TRIPLICATE	KECEIV	<del>(ED</del>	7. If Unit or CA, Agreement Designation
: Type or Well		TINTRIFLICATE			
X Oil Well	Gas Well Other		<b>O</b> CT 11	.'94	8. Well Name and No.
	2. Name or Operator			į.	of well Name and No. Old Ranch Canyon 7 Fed
Santa	Fe Energy Operating	Partners, L.P.	<b>C</b> . C.	D.	9. API Well No. #I
3 Address and To			ARTESIA, C		30-015-28011
550 W. Texas, Suite 1330, Midland, Texas 79701  Location of Well (Footage, Sec., T., R., M., or Survey Description)					10. Field and Pool, or Exploratory Area
(B), 660' FNL and 1980' FEL, Sec. 7, T-22S, R-24E			<u>;</u>	Indian Basin (U. Penn) A	
(27, 500 THE and 1900 FEE, 5ec. 7, 1-225, R-24E				or runair, state	
	· · · · · · · · · · · · · · · · · · ·				Eddy Co, NM
12. CH	HECK APPROPRIATE BOX	(s) TO INDICATE NA	ATURE OF NOTI	CE, REPOR	T. OR OTHER DATA
TY	PE OF SUBMISSION		TYPE	OF ACTION	
	Notice of Intent	Aban	ndonment		Change of Plans
F		Recoi	mpletion		New Construction
<u>A</u>	Subsequent Report		ging Back		Non-Routine Fracturing
	Final Abandonment Notice		ng Repair Ting Casing		Water Shut-Off
			Ran casing &	released	Conversion to Injection  Dispose Water
			rig.		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Propo	osed or Completed Operations (Clearly state a irface locations and measured and true verti	ill pertinent details, and give perti	ment dates, including estimationes pertinent to this most	ted date of starting a	ny proposed work. If well is directionally drilled
			ones pertinent to uns work.	,	
8/19/94:		10.1			
	TD 7-7/8" hole @ 830				
8/20/94:					
	Logging. Begin runn	ning 7" casing.	ing and set 0	8300! EC	A 92001
8/20/94: 8/21/94:	Logging. Begin runn Ran total of 176 jts Cemented w/ 500 sx C	ning 7" casing. 3 7" 26# LT&C cas 21 "H" containing	2 0.8% FL25 and	d 5% salt.	Plug down @
	Logging. Begin runn Ran total of 176 jts Cemented w/ 500 sx C 8:30 a.m. ND BOP's,	ning 7" casing. s 7" 26# LT&C cas Cl "H" containing . NU tubing head	g 0.8% FL25 and & test, ok.	d 5% salt.	Plug down @
	Logging. Begin runn Ran total of 176 jts Cemented w/ 500 sx C	ning 7" casing. s 7" 26# LT&C cas Cl "H" containing . NU tubing head	g 0.8% FL25 and & test, ok.	d 5% salt.	Plug down @
	Logging. Begin runn Ran total of 176 jts Cemented w/ 500 sx C 8:30 a.m. ND BOP's,	ning 7" casing. s 7" 26# LT&C cas Cl "H" containing . NU tubing head	g 0.8% FL25 and & test, ok.	d 5% salt.	Plug down @
	Logging. Begin runn Ran total of 176 jts Cemented w/ 500 sx C 8:30 a.m. ND BOP's,	ning 7" casing. s 7" 26# LT&C cas Cl "H" containing . NU tubing head	g 0.8% FL25 and & test, ok.	d 5% salt.	Plug down @
	Logging. Begin runn Ran total of 176 jts Cemented w/ 500 sx C 8:30 a.m. ND BOP's,	ning 7" casing. s 7" 26# LT&C cas Cl "H" containing . NU tubing head	g 0.8% FL25 and & test, ok.	d 5% salt.	Plug down @
	Logging. Begin runn Ran total of 176 jts Cemented w/ 500 sx C 8:30 a.m. ND BOP's,	ning 7" casing. s 7" 26# LT&C cas Cl "H" containing . NU tubing head	g 0.8% FL25 and & test, ok.	d 5% salt.	Plug down @
	Logging. Begin runn Ran total of 176 jts Cemented w/ 500 sx C 8:30 a.m. ND BOP's,	ning 7" casing. s 7" 26# LT&C cas Cl "H" containing . NU tubing head	g 0.8% FL25 and & test, ok. WOCU.	d 5% salt. Set slips.	Plug down @
	Logging. Begin runn Ran total of 176 jts Cemented w/ 500 sx C 8:30 a.m. ND BOP's,	ning 7" casing. s 7" 26# LT&C cas Cl "H" containing . NU tubing head	g 0.8% FL25 and & test, ok. WOCU.	d 5% salt.	Plug down @ Clean and
	Logging. Begin runn Ran total of 176 jts Cemented w/ 500 sx C 8:30 a.m. ND BOP's,	ning 7" casing. s 7" 26# LT&C cas Cl "H" containing . NU tubing head	g 0.8% FL25 and & test, ok. WOCU.	d 5% salt. Set slips.	Plug down @ Clean and

Sr. Production Clerk 30, 1994 Approved by \_\_\_\_\_\_\_ Conditions of approval, if any: Title Date