Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000

BUREAU OF LAND MANAGEMENT					5. Lease Serial No. NM-78213 6. If Indian, Allottee or Tribe Name 7. If Unit or CA/Agreement, Name and/or No.						
SUNDRY NOTICES AND REPORTS ON WELLS											
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.											
SUBMIT IN TRIPLICATE - Other Instructions on Teverse side											
1. Type of Well	/	- 	9000		। [-						
🔲 Oil Well 🛛 Gas Well 🕻	Other	• • • • • • • • • • • • • • • • • • •	2	<u>'</u>		8. Wel	II Name a	nd No.			
2. Name of Operator Yates Petroleum (77		Walt Canyon AMA Federal #3 9. API Well No.							
3a. Address	finclude are	a code)		30-015-28319							
105 S. 4th St	48-1471			10. Field and Pool, or Exploratory Area							
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)						Indian Basin Upper Penn,					
	FWL of Section 3-T		Unit D.	NWNW)	11. Cou	inty or Pa	rish, State	Asso	с.	
III) IND C 010	IND OF OCCUPANTS						F 1 1	0	NIM		
		NSL Orde		-4388				y Co.,			
12. CHECK AT	PROPRIATE BOX(ES) T	OINDICATE	NATURE	OF NO	TICE, R	EPORT,	OR O	THER DA	ATA		
TYPE OF SUBMISSION	TION										
	Acidize	Deepen		Produ	ction (Start	/Resume)		Water Shu	ıt-Off		
Notice of Intent	Alter Casing	Fracture Tr	eat [Reclai	mation			Well Integ	grity		
f.V)	Casing Repair	New Consti	ruction	Recor	nplete		Ø	Other S	pud, c	onductor,	
X Subsequent Report	Change Plans	Plug and Al		_	· orarily Λb:	andon		etc.	1	-	
Final Abandonment Notice	Convert to Injection	Plug Back		-	Disposal						
Spudded a 12-1/4" 12-1/4" hole to 26 to surface. Resum	" hole from surfacted drilling a 14-3	ce to 40'. 3/4" hole w	Set 40 ith rot	' of	20" co	nducto	or pi	pe and	cemen	amed ted	
NOTE: Notified Ge	ne Hunt with BLM-0	Carlsbad of	spud.								
TD 1654'. Reached of casing set at 1 set at 1607'. Cem	TD at 11:15 AM 2-654'. 1-Texas Par	ttern notch	ned guid	e sho	e set	at 165	54'.	Float	colla	r	
10#/sack gilsonite	lented with 200 sad	2k5 1111XUC1	.0pic, i	eacke	65-35	Poz	ucu.	5#/sac	k sodi	11M	
chloride, 1/4#/sac	$\frac{1}{2}$ (yield 1.54, well)	gnt 14.0) a	nite and	67 o	rel (vi	e1d 2	.04.	veicht	12.5)		
Tailed in with 200	cacks Class C and	ack gilson	(viald	. ∪∧ g 1 34	weigh	1 14 8	8).	PD 8:0	0 PM	•	
2-14-2000. Bumped	l plug to 500 psi	float did	not hol	d. 0	ement	did no	ot ci	rculat	e. WO	С	
7-1/2 hours. Ran	Temperature Surve	v and found	top of	сете	nt at	1300'	. Ra	n 1".	Tagge	d	
cement at 1330'.	Spotted 100 sacks	Class C at	nd 2% Ca	C12.	PD 6:	00 AM	2-15	-2000.	WOC		
2-1/2 hours. Ran	1". Tagged cemen	t at 1330'.	. Spott	ed 72	sacks	Clas	s C a	nd 4%	CaCl2.		
14. I hereby certify that the foregoing is true and correct				CONTINUED ON NEXT PAGE:							
Name (Printed/Typed)				Title Operations Technician							
Rusty Klein		Date March 17 2000 ACCEPTED FOR RECORD									
Signature Kustur	Klein		Date Mar	ch 17	, 2000		100E	TED FI	OR REC	ORD	
1-0	THIS SPACE	FOR FEDERA	L OR STAT	E OFF	ICE USE		M	1D 0 0) GASS		
							1	MIN 75 2	ZUCU		
Approved by			7 itle				Date		001	++	
Conditions of approval, if any, are certify that the applicant holds leg	attached. Approval of this not	ice does not warra	nt or lease			1		BLN	1	7	
which would entitle the applicant to	conduct operations thereon.	in the subject	Office								

CEATEORY

SS \$ \$ SS HAN DULL