

## FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-015-28348

Operator <u>Marble, Inc.</u>		Lease <u>Keystone</u>		Well # <u>5</u>	
Location of Well	Unit <u>B</u>	Section <u>32</u>	Township <u>20</u>	Range <u>28</u>	County <u>Eddy</u>
Drilling Contractor <u>NA</u>	Type of Equipment <u>Rotary</u>				

## APPROVED CASING PROGRAM

\* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	* 13 3/8	54.5		500	550 Circ
12 1/2	* 8 3/8	32		2600	700 Circ
7 7/8	5 1/2	15.5		6700	

## Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
 (Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

## Cementing Program

Size of hole 17 1/2" Size of Casing 13 3/8" Sacks cement required \_\_\_\_\_

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 530' Set 530' Feet of 13 3/8" Inch 48 # Grade 11-40

(New) used csg. @ 530' with \_\_\_\_\_ sacks neat cement around shoe  
 + 550 sax CL. C. additives 1/4# f/oseal, 270cc

Plug down @ 10:00 (AM) (PM) Date 3-6-95

Cement circulated No No. of Sacks -0-

Cemented by B.J. Titan Witnessed by Mike Stubblefield

Temp. Survey ran @ \* (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_

L.C. - 50'

\* Tagged to 34'. Operator will ready mix well to surface.