

RAN 79 JTS 7" 26# & 105 JTS 7", 23#, K-55 LTC CSG TO 8050'.  
FLOAT SHOE @ 8048', FLOAT COLLAR @ 7959'. DU TOOL @ 6368'.  
CMT 1ST STAGE W/310 SX CLASS "C" W/1.2% BA 56, 5 PPS CSE,  
3 PPS KOLSEAL, .6% CD 32, WT 15.35, YIELD 1.32. DROPPED  
BOMB, SHIFTED TOOL, CIRC'D 106 SX TO SURFACE. CIRC'D  
W/RIG PUMPS FOR 4 HRS. CMTS 2ND STAGE W/750 SX 35:65 POZ  
W/6% GCL, 55 NACL, 3 PPS KILSEAL, WT 12.65, YIELD 1.98.  
TAILED IN W/100 SX CLASS "C" W/3 PPS KOLSEAL WT 14.7, YIELD  
1.36. CIRCD 43 SX CMT TO SURFACE.

CLOSED TOOL. FLOATS HELD. SET SLIPS, CUT CSG.  
INSTALLED 7 1/16" 3M TBG HEAD. TESTED SEALS TO 3000 PSI.  
RIG RELEASED @ 0400 HRS 3/28/96.