

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONSERVATION DISTRICT
3. 1st ST.
TESIA, NM 88210-2834

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other Dry Hole

2. Name of Operator

Penwell Energy, Inc. 174380 (915) 683-2534

3. Address and Telephone No.

600 N. Marienfeld Suite 1100, Midland, Texas 79701

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FNL & 1980' FEL, Sec. 7; T22S; R26E, Unit Letter G

5. Lease Designation and Serial No.
NM-064528 (A)

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

18685

8. Well Name and No. Well #1

Rifleman "7" Federal

9. API Well No.

30-015-28858

10. Field and Pool, or Exploratory Area
Wildcat

Happy Valley Bone Spr

11. County or Parish, State

Eddy

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

4-13-96 spotted cement plugs per BLM instructions: Set plug @ 6161'; Cemented with 40 sacks Cl. "C"; plug @ 4,988' cemented w/30 sacks, plug @ 2,300' cemented w/100 sacks + 2% CaCl₂. WOC 3 hours. Tagged plug @ 2,060'. (Witnessed by Jim Amos w/BLM). Set plug @ 350' and cemented w/30 sacks; plug @ 50' to surface - 15 sacks. Released rig @ 6:00 P.M. MST, 4-12-96

4-14-96 Cut off wellhead, installed dry hole marker. Filled in cellar and fenced reserve pit.

Post ID-2
6-14-96
PFA

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

Brenda Coffman

Title

Production Analyst

Date

April 18, 1996

(This space for Federal or State office use)

Approved by

(ORIG. SCD.) JOE G. LARA

Title

PETROLEUM ENGINEER

Date

5/20/96

Conditions of approval, if any: