

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

clsf
up

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-29351

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

LOUIS DREYFUS NATURAL GAS CORP.

3. Address of Operator

14000 Quail Springs Parkway, Ste. 600, OKC, OK 73134

4. Well Location

Unit Letter E : 1715 Feet From The North Line and 1160 Feet From The West Line

Section 29

Township 22S

Range 26E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, CR, etc.)

3412'

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Run 10-3/4" casing. ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/13/97 RU strap shoe & float collar, ran 37 jts. (1654') 10-3/4" J-55 ST&C R3 casing, shoe @ 1652', float @ 1602'. Dowell cemented with 150 sx RFC in a 43 bbl. slurry + 900 sx Class "C", 4% gel, 2% CC in a 280 bbl. slurry. Tail in with 200 sx Class "C" Neat, 2% CC in a 47 bbl. slurry. Calculated TOC @ 667'. Top off with 258 sx Class "C" Neat, 4% CC. Full returns while cementing. Circulate 3 bbls. excess, 13 sx to reserve pit. Cement in place @ 1:00 p.m. 3/13/97. WOC. Cut off 16" csg. and orange peel back to 10-3/4" csg., cut off 10-3/4" csg. & install wellhead test to 1000 psi, test OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Raylene Smith

title Regulatory Tech.

DATE 4/21/97

(405) 749-

TELEPHONE NO.

5251

TYPE OR PRINT NAME

Raylene Smith

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY

TITLE

DATE

APR 28 1997