

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a ~~public~~ reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 660' FWL of Section 34-T22S-R23E (Unit M, SWSW)

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-9194

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Sacahuiste KE Federal #2

9. API Well No.

30-015-29432

10. Field and Pool, or Exploratory Area

Indian Basin Yeso South

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Resume drilling, surface casing & cement

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Resumed drilling a 14-3/4" hole with rotary tools at 9:30 PM 8-23-97. Lost all returns at 135'. Cut window in conductor and cemented with 10 yards ready-mix. WOC. Cemented with 10 yards ready-mix. WOC. Drilled cement and tagged cement at 125'. Resumed drilling.

TD 450'. Reached TD at 9:30 AM 8-25-97. Ran 11 joints of 11-3/4" 42# H-40 and STC (474.61') of casing set at 450'. 1-Texas Pattern notched guide shoe set at 450'. Insert float set at 403'. Cemented with 250 sacks "H", 10% A-10B, 1/2#/sack cellohane and 10% sack gilsonite and 2% CaCl2 (yield 1.52, weight 14.5). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 5:00 PM 8-25-97. Bumped plug to 750 psi, OK. Cement did not circulate. WOC 2 hours. Ran 1". Tagged cement at 67'. Spotted 60 sacks "C" and 4% CaCl2. PD 10:00 PM 8-25-97. Circulated 12 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 7:00 AM 8-26-97. WOC 14 hours. Reduced hole to 11". Resumed drilling.

NOTE: Job witnessed by Gene Hunt w/BLM-Carlsbad.

ACCEPTED  
SEP 10 1997

4. I hereby certify that the foregoing is true and correct

Signed Rusty Klein  
(This space for Federal or State office use)

Title Operations Technician

Date Sept. 5, 1997

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

Date \_\_\_\_\_