

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Ei Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-29539
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	K-3402
7. Lease Name or Unit Agreement Name	Stonewall DD State
8. Well No.	3
9. Pool name or Wildcat	Burton Flat Morrow Gas
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	3266' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter E : 1650 Feet From The North Line and 990 Feet From The West Line

Section 20 Township 20S Range 28E NMPM Eddy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3266' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Resume drilling, surface casing & cmt ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Resumed drilling a 17-1/2" hole with rotary tools at 12:00 midnight 5-14-97 (12:00 AM 5-15-97).

TD 542'. Reached TD at 7:30 PM 5-15-97. Ran 12 joints of 13-3/8" 48# H-40 8rd ST&C (546.87') of casing set at 542'. 1-Texas Pattern notched guide shoe set at 542'. Insert float set at 497'. Cemented with 50 sacks Premium (scavenger cement) (yield 2.62, weight 11.6) and 300 sacks Halliburton Lite Premium Plus, 2% CaCl₂, 5#/sack gilsonite and 1/4#/sack flocele (yield 1.96, weight 12.5). Tailed in with 200 sacks Premium Plus with 2% CaCl₂ (yield 1.32, weight 14.8). PD 1:30 AM 5-15-97. Bumped plug to 400 psi, OK. Circulated 140 sacks. WOC. Nippled up and tested to 3000 psi for 30 minutes, OK. Drilled out at 7:30 PM 5-16-97. WOC 18 hours. Reduced hole to 12-1/4". Resumed drilling. NOTE: Bryan Arrant w/OCD-Artesia approved casing point change from 600' to 542' due to drilling rate dropping.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE May 20, 1997
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-147

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

MAY 27 1997

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: