

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

N.M. O. Cons. Division  
811 S. 1st  
Artesia, NM

FORM APPROVED  
Bureau No. 1004-0135  
Expires November 30 2000

C151

5. Lease Serial No.  
210-2834 LC-06293 064391 B

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator  
Marathon Oil Company

3a. Address  
P.O. Box 552 Midland, TX 79702

3b. Phone No. (include area code)  
915/687-8356

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
2300' FSL & 2000' FEL  
SEC. 29, T-21-S, R-24-E

7. If Unit or CA/Agreement, Name and/or No.  
INDIAN HILLS UNIT

8. Well Name and No.  
INDIAN HILLS UNIT #14

9. API Well No.  
30-015- - 30624

10. Field and Pool, or Exploratory Area  
INDIAN BASIN

11. County or Parish, State  
EDDY NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

ACCEPTED FOR RECORD  
MAY 28 1999  
BLM

☐ Acidize  
☐ Alter Casing  
☐ Casing Repair  
☐ Change Plans  
☐ Convert to Injection

TYPE OF ACTION

☐ Deepen  
☐ Fracture Treat  
☐ New Construction  
☐ Plug and Abandon  
☐ Plug Back  
☐ Production (Start/Resume)  
☐ Reclamation  
☐ Recomplete  
☐ Temporarily Abandon  
☐ Water Disposal  
☐ Water Shut-Off  
☐ Well Integrity  
☒ Other  
SPUD &  
DRILLING

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

5/7/99, MIRU McVay # 4, Spud 12.25" hole @ 1030 hrs, 5/7/99. Drilled to 1230'. Ran 29 jts, 9.625", 36 #, K-55, STC casing to 1230', shoe @ 1230', Float collar @ 1191'. Cemented w/ 200 sx Thixset Wt-14.0, yield- 1.52, followed by 155 sx. Premium plus Wt -- 12.4, yield - 2.02. Tailed in w/ 200 sx premium plus neat, Wt 14.8, yield - 1.34. Did not circulate cement. Tagged cement @ 788'. Cemented w/ 1" tubing, 165 sx, Class "C" in 4 stages to 475'. Dumped 10 CY of pea gravel in annulus. Unable to get 1" past 73'. Cemented to surface w/ 20 sx cement. Welded 9.625" SOW X 11" 3M casing head. Tested weld to 1500 psi. N.U. 11" 3M dual ram and annular BOPE, choke manifold and kill line. Tested BOPE to 3000/300 psi. Tested annular to 2000 psi. P.U. 8.75" bit and TIH to TOC @ 1178', tested casing to 1000 psi. Drilled shoe and formation to 8150' TD @ 1200 hrs 5/19/99. R.U. Schlumberger, ran Platform - Express w/ HALS/NGT 8041' - Surface.

Changed rams to 7", ran 75 jts, 26 #, K-55, 105 jts, 23 #, K-55, 2 jts, 26 #, K-55 LTC casing to 8200'. Shoe @ 8150', float collar @ 8106', ECP @ 5970', D.V. @ 5960'. Cemented 1st. stage w/ 150 sx Premium Plus w/ 1400 Scf N2, Wt - 9.2, yield - 1.18. Tailed in w/ 360 sx Premium Plus foamed w/ 900 SCF N2, Wt - 13.2, yield 1.18. Set ECP & dropped bomb, opened D.V. tool @ 5960', circulated out gas and water, had full returns, circulated out 15 sx cement. Cemented 2nd stage w/ 550 sx. Interfil C w/ .25 p.p.s. flocele, 3 p.p.s. Gilsonite, .2% Halad - 22, Wt - 11.9, yield - 2.47. Tailed in w 100 sx neat. Plug down @ 0145 hrs, 3/20/99. Circulated 14 sx to surface.

ND BOPE and set slips, NU 11" 3M X 7 1/16" 3M tubing spool. Tested seals to 1000 psi. Released rig @ 2000 hrs 5/23/99.

14. I hereby certify that the foregoing is true and correct  
Name (Printed/Typed)

R. J. LONGMIRE

Title

DRILLING SUPERINTENDENT

Date

5/24/99

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)