

C/S P
JP

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240
DISTRICT II
P.O. Drawer 100, Artesia, NM 88210
DISTRICT III
1000 Rio Brazos Rd, Aztec, NM
87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-30886 ✓
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name EDDY "FV" STATE COM. (25202)
8. Well No. 4
9. Pool name or Wildcat BURTON FLAT (MORROW) (73280)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well
 Oil Well Gas Well Other proposed gas well

2. Name of Operator (6137)
DEVON ENERGY CORPORATION (NEVADA)

3. Address of Operator
20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611
Wally Frank X4595

4 Well Location
Unit Letter P : 660 Feet From The SOUTH Line and 760 Feet From The EAST Line

Section 25 Township 20S Range 27E NMPM EDDY County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
GL 3322

Check Appropriate Box To Indicate Nature Of Notice, Report, Or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK PLUG AND ABANDON

TEMPORARILY ABANDON CHANGE PLANS

PULL OR ALTER CASING

OTHER:

SUBSEQUENT REPORT OF:

REMEDIAL WORK ALTERING CASING

COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT

CASING TEST AND CEMENT JOB

OTHER: Spud, setting casing strings, WOCU

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103.

This well spud on 01-13-2000 at 1300 hrs and drld a 17 1/2" hole to 501'. On 01-15-2000 ran 13 jts 13 3/8" 48# H-40 ST&C csg, set at 500'; cemented w/175 sx 35/65/6 Pozmix "C" + 300 sx Class "C"; TOC at surface. WOC 31 hrs.

Drld 12 1/4" hole to 2624'. On 01-19-2000 ran 60 jts 9 5/8" 36# J-55 ST&C csg, set at 2623'; cemented w/600 sx 35/65/6 Pozmix "C" + 400 sx Class "C"; TOC at surface. WOC 23 hrs.

Drld to 8 3/4" hole. Reached TD 11,500' at 1930 hrs 02-10-2000. On 02-11-2000 Schlumberger ran Platform Express Three Detector Litho-Density/Compenated Neutron/NG and Azimuthal Laterolog Micro-CFL/GR logs.

On 02-13-2000 ran 267 jts 5 1/2" 17# L-80 and 15.5# J-55 LT&C csg, set at 11,500' w/DV tool at 9013'; cemented w/625 sx Super "C" Mod + 175 sx Class "H" + 450 sx 35/65/6 Pozmix "H" + 100 sx Class "H"; preceded cement by 20 BW + 40 bbls TurboFlow3; TOC calc at 6500'. Released rig at 0700 hrs 02-14-2000. WOCU.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Candi R. Graham TITLE ENGINEERING TECHNICIAN DATE February 17, 2000

TYPE OR PRINT NAME Candi Graham TELEPHONE NO. (405) 235-3611

(This space for State use)

Approved by Jim W. Green TITLE District Supervisor DATE 2-25-00

Conditions of approval, if any: