

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Dist. 2

1801 W. Street, Suite 100

FORM APPROVED
OMB No. 1004-0135
Expires November 30, 2000**SUNDRY NOTICES AND REPORTS ON WELLS**
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.***SUBMIT IN TRIPLICATE - Other Instructions on reverse side**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Yates Petroleum Corporation

3a. Address

105 S. 4th St. - Artesia, NM 88210

3b. Phone No. (include area code)

505-748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FSL & 660' FEL of Section 11-T21S-R21E (Unit I, NESE)

5. Lease Serial No.

NM-100521

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.

Mule Deer ATU Federal Com #2

9. API Well No.

30-015-31223

10. Field and Pool, or Exploratory Area

Wildcat Morrow

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other Intermediate
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	<u>casing & cement</u>
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleting horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

TD 2036'. Reached TD at 1:30 PM 8-20-2000. Ran 49 joints of 8-5/8" 24# J-55 (2042.98') of casing set at 2036'. 1-regular guide shoe set at 2035'. Float collar set at 1991'. Cemented with 200 sacks Thixad, 1% CaCl₂, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.52, weight 14.6) and 800 sacks Poz C (65-35-6), 5#/sack salt, 1/4#/sack celloflake and 5#/sack gilsonite (yield 12.8, weight 1.90). Tailed in with 200 sacks Class C with 2% CaCl₂ (yield 1.32, weight 14.8). PD 12:30 AM 8-20-2000. Bumped plug to 470 psi, OK. Cement did not circulate. WOC 6 hours and ran Temperature Survey and found top of cement at 975'. Ran 1". Tagged cement at 980'. Spotted 75 sacks Class C with 4% CaCl₂. PD 8:30 AM 8-20-2000. WOC 1-1/2 hour. Ran 1". Tagged cement at 916'. Spotted 75 sacks Class C with 4% CaCl₂. PD 10:30 AM 8-20-2000. WOC 3 hours. Ran 1". Tagged cement at 675'. Spotted 75 sacks Class C with 4% CaCl₂. PD 2:15 PM 8-20-2000. WOC 1-1/2 hours. Ran 1". Tagged cement at 515'. Spotted 75 sacks Class C with 4% CaCl₂. PD 4:00 PM 8-20-2000. WOC 1-1/2 hour. Ran 1". Tagged cement at 430'. Spotted 75 sacks Class C with 4% CaCl₂. PD 6:00 PM 8-20-2000. WOC 1 hour. Ran 1". Tagged cement at 419'. Spotted 75 sacks Class C with 4% CaCl₂. PD 8:00 PM 8-20-2000. WOC 1-1/2 hour.

14. I hereby certify that the foregoing is true and correct

CONTINUED ON NEXT PAGE:

Name (Printed/Typed)

Rusty Klein

Title Operations Technician

Signature

Date

Dec. 3, 2000

ACCEPTED FOR RECORD THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

(ORIG. SGD.) DAVID R. GLASS

Title

Date


Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

YATES PETROLEUM CORPORATION
Mule Deer ATU Federal Com #2
Section 11-T21S-R21E
Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

Ran 1". Tagged cement at 330'. Spotted 90 sacks Class C with 2% CaCl₂. PD 10:00 PM 8-20-2000. Circulated 10 sacks to pit. WOC. Nippled up and tested to 3000# for 15 minutes, OK. Drilled out at 5:30 AM 8-21-2000. WOC 29 hours. Reduced hole to 7-7/8". Resumed drilling.



Rusty Klein
Operations Technician
Dec. 3, 2000

