

on chokeline and all inside valves closed off choke-manifold cross - pressure applied as before.

Test #3 Pressured to 5000# with pressure steady and holding for the thirteen minutes of test.

NO VISIBLE LEAK. PRESSURE STEADY AT APPROXIMATELY 5000#.

---

TESTING: Blind Rams with outside valve closed off stack on kill line and all inside valves closed off choke-manifold cross - pressure applied as before.

Test #4 Pressured to 5000# with leak to flange between inside valve and outside valve off stack on kill line. Tightened.

Test #5 Repeated test. Pressured to 5000# with leak to flange between spacer spool and casing spool. Tightened.

Test #6 Repeated test. Pressured to 5000# with loss of approximately 100# during first ten minutes then leveling out for remaining one minute of test.

NO VISIBLE LEAK. PRESSURE LEVELING OUT TOWARDS APPROXIMATELY 4900#.

Released pressure to 1000# and opened outside valve off stack on kill line and applied pressure against check valve off stack on kill line; repressured to 5000# with loss of approximately 100# during first five minutes then leveling out for remaining one minute of test.

NO VISIBLE LEAK. PRESSURE LEVELING OUT TOWARDS APPROXIMATELY 4900#.

---

TESTING: Lower Pipe Rams with all inside valves closed next to stack - pressure applied down drill pipe.

Test #7 Pressured to 600# and released air; repressured to 200# and