

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>BELCO PETROLEUM CORP</u>		Lease <u>MARTIN COM</u>		Well # <u>1</u>	
Location of Well	Unit <u>F</u>	Section <u>20</u>	Township <u>22-S</u>	Range <u>27-E</u>	County <u>EDDY, N.M.</u>
Drilling Contractor	<u>MCVAY</u>		Type of Equipment <u>ROTARY</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>20</u>	<u>16"</u>	<u>45 #</u>		<u>350</u>	<u>475 CIRC</u>
<u>13 3/4</u>	<u>10 3/4"</u>	<u>45.5 #</u>		<u>2000</u>	<u>950 CIRC</u>
<u>9 1/2"</u>	<u>7 3/8"</u>	<u>26.4 #</u>		<u>8950</u>	<u>350 - 7000'</u>

Casing Data: 6 1/2" W5 1/2" LINER. 20 # 11,700' 250 - 2500'

INTERM.
Surface 48 joints of 10 3/4" inch 40.5 # Grade K.55-NEW ARMCO STEEL

(Approved) (~~Rejected~~)

Inspected by Leon Bergstrom date 2-19-75

Cementing Program

Size of hole 13 3/4" Size of Casing 10 3/4" Sacks cement required 1150

Type of Shoe used GUIDE Float collar used YES Btm 3 jts welded THREAD LOCKED

TD of hole 1940 KB Set Feet of 10 3/4 Inch 40.5 # Grade K.55

New ~~old~~ csg. @ 1927 G.L. with 200 sacks neat cement around shoe w/ 2 1/2 CIRC.
+ 950 sax HOWCO LITE additives 5 #/sx GILSONITE

Plug down @ 3 25 (PM) Date 2-19-75

Cement circulated YES No. of Sacks 40 SX

Cemented by HALLIBURTON Witnessed by Leon Bergstrom

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: T.D. SURFACE 360' KB-347' G.L. RAN 3 JTS NEW API-16" X 64" K.55, 8 RD

STEC RANGE 3 CSG. SET @ 347' G.L. CMTD W/ 475 SX CLASS C W/ 3 1/2" CIRC

CIRC EST 50 BEIS CMT TO PIT. PLUG DN @ 1 30 PM. 2-14-75 Leon Bergstrom