NO. OF COPIES RECEIVED	
DISTRIBUTION	Form C-103
	Supersedes Old C-102 and C-103
NEW MEXICO OIL CONFET ATION CONNINCE	Effective 1-1-65
U.S.G.S.	5a. Indicate Type of Lease
AUG 1 3 1975	State Fee X
OPERATOR / AUG 1 3 19/3	5. State Oil & Gas Lease No.
	or oracle our d das Ecase Mo.
SUNDRY NOTICES AND REPORTS ON WELLS A. DEFICE	annonno de la constanta de la
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT _" (FORM C-101) FOR SUCH PROPOSALS.)	
1. OIL GAS TY	7. Unit Agreement Name
WELL NELL A OTHER-	
2. Name of Operator	8. Farm or Lease Name
Champlin Petroleum Company 3. Address of Operator	Wilson Gas Com.
	9. Well No.
701 Wilco Building, Midland, Texas 79701	1
	10. Field and Pool, or Wildcat
UNIT LETTER G . 1980 FEET FROM THE NORTH LINE AND 1980 FEET FRO	Undesignated-Wolfcamp
THE East LINE SECTION 1 TOWNSHIP 22-S 27-E	
THE East LINE, SECTION 1 TOWNSHIP 22-S RANGE 27-E NMPI	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3136 DF	
16	Eddy ///////
Check Appropriate Box To Indicate Nature of Notice, Report or O	
NOTICE OF INTENTION TO.	ther Data IT REPORT OF:
NOTICE OF INTENTION TO: SUBSEQUEN	IT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	IT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS.	IT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS.	IT REPORT OF:
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING CHANGE PLANS SUBSEQUEN REMEDIAL WORK COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JOB X	IT REPORT OF: ALTERING CASING
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS. PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB X OTHER COMPletion	IT REPORT OF: ALTERING CASING PLUG AND ABANDONMENT
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS. PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB X OTHER COMPLETION	IT REPORT OF: ALTERING CASING PLUG AND ABANDONMENT
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS. PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB X OTHER COMPletion 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703.	ALTERING CASING PLUG AND ABANDONMENT
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) SEE RULE 1103. Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and c	ALTERING CASING PLUG AND ABANDONMENT g estimated date of starting any propose emented with 450 sacks
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) SEE RULE 1703. Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and conclusions H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Cl	ALTERING CASING PLUG AND ABANDONMENT g estimated date of starting any propose emented with 450 sacks ass H w/8% salt and
PERFORM REMEDIAL WORK PLUG AND ABANDON COMMENCE DRILLING OPNS. TEMPORARILY ABANDON CHANGE PLANS CASING TEST AND CEMENT JOB COMPLETION OTHER COMPLETION 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and completed Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4%	ALTERING CASING PLUG AND ABANDONMENT g estimated date of starting any propose emented with 450 sacks ass H w/8% salt and lested casing to 1600#
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) SEE RULE 1703. Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and completed Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2/sack pump plug down @ 5:15 am 6-15-75. WOC 123 hours. The formal work is the first transfer of the fir	ALTERING CASING PLUG AND ABANDONMENT [g estimated date of starting any propose emented with 450 sacks ass H w/8% salt and ested casing to 1600# 26, 9533, 9547, 9757
PERFORM REMEDIAL WORK PLUG AND ABANDON COMMENCE DRILLING OPNS. TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. OTHER COMPletion 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) SEE RULE 1703. Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and c Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Cl 3/4% CFR-2/sack pump plug down @ 5:15 am 6-15-75. WOC 123 hours. T for 30 minutes, tested ok. Perforated Wolfcamp 9457, 9518, 9524, 959758, 9911, 9914, 9917 and 9920 (12 holes). Treated perfs 9457-9547	ALTERING CASING PLUG AND ABANDONMENT [g estimated date of starting any propos emented with 450 sacks ass H w/8% salt and ested casing to 1600# 26, 9533, 9547, 9757, with 2900 gals, DS-30
PERFORM REMEDIAL WORK PLUG AND ABANDON COMMENCE DRILLING OPNS. TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. OTHER COMPletion 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) SEE RULE 1703. Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and c Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Cl 3/4% CFR-2/sack pump plug down @ 5:15 am 6-15-75. WOC 123 hours. T for 30 minutes, tested ok. Perforated Wolfcamp 9457, 9518, 9524, 959758, 9911, 9914, 9917 and 9920 (12 holes). Treated perfs 9457-9547	ALTERING CASING PLUG AND ABANDONMENT [g estimated date of starting any propos emented with 450 sacks ass H w/8% salt and ested casing to 1600# 26, 9533, 9547, 9757, with 2900 gals, DS-30
PERFORM REMEDIAL WORK PULL OR ALTER CASING T. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) SEE RULE 1703. Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and c Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Cl 3/4% CFR-2/sack pump plug down @ 5:15 am 6-15-75. WOC 123 hours. T for 30 minutes, tested ok. Perforated Wolfcamp 9457, 9518, 9524, 95 9758, 9911, 9914, 9917 and 9920 (12 holes). Treated perfs 9457-9547 15% acid. Staged with 10 ball sealers. Treated perfs. 9757-9920 w/	ALTERING CASING PLUG AND ABANDONMENT [g estimated date of starting any propos emented with 450 sacks ass H w/8% salt and ested casing to 1600# 26, 9533, 9547, 9757, with 2900 gals. DS-30 2000 gals. DS-30
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and concern the concern that the concern t	ALTERING CASING PLUG AND ABANDONMENT [g estimated date of starting any propos emented with 450 sacks ass H w/8% salt and ested casing to 1600# 26, 9533, 9547, 9757, with 2900 gals. DS-30 2000 gals. DS-30 15% d water. Shut well in
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER TO DESCRIBE Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) SEE RULE 1703. Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and c Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Cl 3/4% CFR-2/sack pump plug down @ 5:15 am 6-15-75. WOC 123 hours. T for 30 minutes, tested ok. Perforated Wolfcamp 9457, 9518, 9524, 95 9758, 9911, 9914, 9917 and 9920 (12 holes). Treated perfs 9457-9547 15% acid. Staged with 10 ball sealers. Treated perfs. 9757-9920 w/acid, staged ball sealers. Swab tested well, recovered 32 bbls. loa for 11½ hours. Flowed well 1 hour recovered 24 barrels condensate as	ALTERING CASING PLUG AND ABANDONMENT [g estimated date of starting any propos emented with 450 sacks ass H w/8% salt and ested casing to 1600# 26, 9533, 9547, 9757, with 2900 gals. DS-30 2000 gals. DS-30 15% d water. Shut well in
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING THANGE PLANS TO Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and concluses H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4#	ALTERING CASING PLUG AND ABANDONMENT [g estimated date of starting any propos emented with 450 sacks ass H w/8% salt and ested casing to 1600# 26, 9533, 9547, 9757, with 2900 gals. DS-30 2000 gals. DS-30 15% d water. Shut well in nd 2 barrels load water ug set at 9941'. Acid
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) SEE RULE'1703. Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and concluses H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack a	ALTERING CASING PLUG AND ABANDONMENT [g estimated date of starting any propose emented with 450 sacks ass H w/8% salt and ested casing to 1600# 26, 9533, 9547, 9757, with 2900 gals. DS-30 2000 gals. DS-30 15% d water. Shut well in nd 2 barrels load water up set at 9941'. Acid
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING THANGE PLANS TO Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and concluses H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4#	ALTERING CASING PLUG AND ABANDONMENT [g estimated date of starting any propose emented with 450 sacks ass H w/8% salt and ested casing to 1600# 26, 9533, 9547, 9757, with 2900 gals. DS-30 2000 gals. DS-30 15% d water. Shut well in nd 2 barrels load water up set at 9941'. Acid
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) SEE RULE'1703. Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and collass H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and	ALTERING CASING PLUG AND ABANDONMENT [g estimated date of starting any propose emented with 450 sacks ass H w/8% salt and ested casing to 1600# 26, 9533, 9547, 9757, with 2900 gals. DS-30 2000 gals. DS-30 15% d water. Shut well in nd 2 barrels load water up set at 9941'. Acid
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING TOTHER TOTHE	ALTERING CASING PLUG AND ABANDONMENT [g estimated date of starting any propose emented with 450 sacks ass H w/8% salt and ested casing to 1600# 26, 9533, 9547, 9757, with 2900 gals. DS-30 2000 gals. DS-30 15% d water. Shut well in nd 2 barrels load water up set at 9941'. Acid
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and collass H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sack	emented with 450 sacks ass H w/8% salt and ested casing to 1600#26, 9533, 9547, 9757, with 2900 gals. DS-30 2000 gals. DS-30 15% d water. Shut well in nd 2 barrels load water up set at 9941! Acid
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and collass H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sack	ALTERING CASING PLUG AND ABANDONMENT [g estimated date of starting any propose emented with 450 sacks ass H w/8% salt and ested casing to 1600# 26, 9533, 9547, 9757, with 2900 gals. DS-30 2000 gals. DS-30 15% d water. Shut well in nd 2 barrels load water up set at 9941'. Acid
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and collass H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sack	emented with 450 sacks ass H w/8% salt and ested casing to 1600#26, 9533, 9547, 9757, with 2900 gals. DS-30 2000 gals. DS-30 15% d water. Shut well in nd 2 barrels load water up set at 9941! Acid
PLUG AND ABANDON PULL OR ALTER CASING TEMPORARILY ABANDON PULL OR ALTER CASING Drilled 7-7/8" hole to 10,043' where 4-1/2" 11.6# csg. was set and contains H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocele/sack and 600 sacks Class H w/8% salt, 3/4% CFR-2 and 1/4# flocel	ALTERING CASING PLUG AND ABANDONMENT g estimated date of starting any proposed emented with 450 sacks ass H w/8% salt and ested casing to 1600# 26, 9533, 9547, 9757, with 2900 gals. DS-30 2000 gals. DS-30 15% d water. Shut well in nd 2 barrels load water ug set at 9941'. Acid 00 gals. Westpad "A"
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING TOTHER TOTHE	emented with 450 sacks ass H w/8% salt and ested casing to 1600#26, 9533, 9547, 9757, with 2900 gals. DS-30 2000 gals. DS-30 15% d water. Shut well in nd 2 barrels load water.

TITLE District Clerk

DATE 8-12-75

AUG 13 1975

CONDITIONS OF APPROVAL, IF ANY: