

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

OCT 5 1976

**O. C. C.
ARTESIA, OFFICE**

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	K-6010

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name Willow Lake Unit
2. Name of Operator Aminoil USA, Inc.	8. Farm or Lease Name Willow Lake Unit
3. Address of Operator 600 Western United Life Bldg., Midland, Texas 79701	9. Well No. 2
4. Location of Well UNIT LETTER <u>J</u> , <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>16</u> TOWNSHIP <u>24-S</u> RANGE <u>28-E</u> NMPM.	10. Field and Pool, or Village Willow Lake-Atoka Gas
15. Elevation (Show whether DF, RT, GR, etc.) 3023 GL	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Sidetrack Junk</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-2-76 Set 150 sks. Class "H" cmt. plug from 3510-3720 KB.
Drilled to 3568 - cement did not firm up.
6-6-76 Set 135 sks. Class "C" cmt. plug from 3710 to 3485.
6-7-76 Drilled firm cement from 3465 to 3550.
P.O.O.H. and P.U. Dyna Drill with 2° bent sub.
6-8-76 Drilled and opened hole with Dyna Drill from 3560 to 3598.
Dev. at 3625 - 1 3/4°.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. E. Stauffer TITLE Sr. Drilling Engineer DATE 10-4-76

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE OCT 6 1976

CONDITIONS OF APPROVAL, IF ANY: