

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 38, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 38. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Socks Cement". Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POHOUTS ZONES:			38. GEOLOGIC MARKERS			
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; COBED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES						
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Delaware	4035	4130	DST #1 - 10"-60" 60" 180"; Strong blow and increased throughout initial flow recovered 150' of drilling mud, MCF recovered: none IHP 1823 FHP 1823 IFP 117 FFP 58-131 ISIP 1808 FSIP 1823 BHT 108°F	Delaware Bone Spring Canyon Strawn Atoka Morrow	1840 5500 10125 10425 10625 11125	(+1685) (-1975) (-6600) (-6900) (-7100) (-7600)
Morrow	11572	11777	DST #2 - 15"-90"-90"-240" 3/4" BHC 3/8" SC Weak blow of air. Gas to surface in 83 min. on second flow. Stabilized 10 MCFPD, recovered 1000' water blanket plus 300' GCDM, sampler recovery 1.4 cf of gas at 400 psi plus 1800 cc gas cut mud IHP 5891 FHP 5891 IFP 577 FFP 647 ISIP 4641 FSIP 4664 BHT 210°F.			